

# Product data sheet

Specifications



## APC Smart-UPS X, Line Interactive, 750VA, Rack/tower convertible 2U, 230V, 8x C13 IEC, SmartSlot, Extended runtime

SMX750I

### Overview

**Presentation** Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

**Lead time** Usually Ships within 2 Weeks

### Main

**Main Input Voltage** 230 V

**Other Input Voltage** 220 V  
240 V

**Main Output Voltage** 230 V

**Rated power in W** 600 W

**Rated power in VA** 750 VA

**Input Connection Type** IEC 320 C14

**Nb of power socket outlets** 8 IEC 320 C13  
2 IEC Jumpers

**Number of rack unit** 2U

**Cable length** 1.83 m

**Number of cables** 1

**Battery type** Lead-acid battery

**Provided equipment** CD with software  
Documentation CD  
Installation guide  
Rack mounting brackets  
Removable support feet  
Smart UPS signalling RS-232 cable  
User manual

### General

**Number of power module filled slots** 0

**Number of power module free slots** 0

**Product web sub-family** Extended run

**Redundant** No

### Physical

**Colour** Black

Height	8.9 cm
Width	43.2 cm
Depth	49 cm
Net weight	22.05 kg
Mounting preference	Lower
Mounting mode	Rack-mounted with kit
Two post mountable	1
USB compatible	No

## Input

Input voltage limits	151...302 V adjustable 160...286 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Harmonic distortion	Less than 5 %
Maximum configurable power in VA	750 VA
Maximum configurable power in W	600 W
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

## Conformance

Product certifications	CE RCM VDE EAC
Standards	EN/IEC 62040-1 EN/IEC 62040-2

## Environmental

Acoustic level	40 dBA
Heat dissipation	69 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

## Batteries & Runtime

Extended runtime	0
Number of battery filled slots	1
Number of battery free slots	1
Battery recharge time	3 h

Number of battery replacement quantity	1
Overcurrent protection	60 A
Battery life	3...5 year(s)
Battery power in VAH	312 VAh runtime
Battery charger power	104 W rated
Battery option	SMX48RMBP2U 1 938 VAh SMX48RMBP2U 2 1563 VAh SMX48RMBP2U 3 2188 VAh SMX48RMBP2U 4 2613 VAh SMX48RMBP2U 5 3438 VAh

## Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Control panel	Multifunction LCD status and control console
Free slots	1

## Surge Protection and Filtering

Surge energy rate	645 J
Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

Package 1 Weight	26.5 kg
Package 1 Height	24.6 cm
Package 1 width	58.9 cm
Package 1 Length	62 cm
Number of Units in Package 3	8

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---