

Data Sheet Fujitsu SL23T-1 LED Display

Advanced Display: 58.4 cm (23-inch) widescreen Lifestyle design and advanced entertainment features

The SL23T-1 LED comes in a 16:9 format with an eye-catching piano black ultra-slim design. With the 3 ms response time and the ultra high 5,000,000:1 contrast ratio (ACR) it is the perfect display for home entertainment. There is no compromise in picture quality and energy efficiency. It is intuitive to handle thanks to sensor keys and support languages.

Widescreen display with LED backlit panel in optimum 16:9 movie format

1920 x 1080 Full HD resolution for ultimate entertainment and work experience

3 ms fast response time for internet, office, gaming and more

Touch sensor keys for smart adjustments

2 x HDMI (CEC-compliant), D-Sub for high flexibility

< 1W/inch typical power consumption and Energy Star compliant

Due to integrated speakers no further accessories needed

































Technical details

Special features	
special leatures	LED backlight panel, 6 + 1 touch sensor keys, ECO Status LED: 3 colors for 3 modes, keep aspect ratio option
Stand details	LED Dacklight parter, 0 1 1 touch sensor keys, Eco status EED. 3 colors for 3 modes, keep aspect ratio option
Stand details	removable
Tilt angle	- 5° / + 15°
	-3 / + 13
Picture performance	TNUED
Panel and backlit	TN/LED
Contrast - typical	1000:1
Contrast - advanced	5,000,000:1
Response time typical	5 ms
Response time gray to gray typical	3 ms
/iewing angle (h/v) - typical	176°/170°
Color performance	16.7 million colors (Hi-FRC)
Brightness - typical	250 cd/m
Size and resolution	
Aspect ratio	16:9
Diagonal Size	58.4 cm (23-inch)
Resolution (native)	1920 x 1080 pixel (recommended)
Resolution (interpolated)	1920 x 1080 pixel, 1680 x 1050 pixel, 1600 x 900 pixel, 1440 x 900 pixel, 1366 x 768 pixel, 1280 x 1024 pixel, 1280 x 800 pixel, 1280 x 720 pixel, 1024 x 768 pixel, 800 x 600 pixel, 720 x 400 pixel, 640 x 480 pixel
Video modes	1080i/p, 720i/p, 576i/p, 480i/p
Pixel Pitch	0.265 mm
requencies	
Horizontal analog	31 kHz to 94 kHz
Horizontal digital	15 kHz to 83 kHz
/ertical	56 - 76 Hz
requencies - bandwidth	225 MHz
Connectivity	ELS IIII E
HDMI	2 x HDMI
/GA/D-SUB	1 x D-SUB
Audio signal output	S/PDIF (optical)
Audio signal input	3.5 mm stereo phone jack
	· · ·
Audio sound output	2 x 1 W
HDMI audio	Yes
OSD Languages and setting options Languages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish
Brightness / Contrast	Brightness, Contrast, Black level, Auto level
Color	6500K, 7500K, 9300K, Native, sRGB, Custom Color
mage adjust	H-Position, V-Position, Sharpness, Clock, Phase
Audio	Mute, Volume
nformation	Resolution/mode, Signal input
Power consumption (typical)	
Soft switch off	0.5 W
Power save mode	0.5 W
Operating with EPA settings	21 W
Operating maximum brightness	24 W
Power supply display	external
Power notes	without sound;

Electrical values	
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Protection class	1
Compliance	
Europe	CE, RoHS, WEEE, IT-Eco-Declaration
Russia	GOST
USA/Canada	FCC Class B, cUL
Australia/New Zealand	C-Tick
Saudi Arabia	SASO
Global	TCO Displays 5.1, ENERGY STAR® 5.0, EPEAT® Silver (dedicated regions), ISO9241-307 (Pixel fault class I)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx
Quality and Reliability	
MTBF (demonstrated)	50.000 h
Dimensions / Weight / Environmental	
Dimension without stand $(W \times D \times H)$	548 x 43 x 343.5 mm
Dimension with stand (W x D x H)	548 x 189.2 x 404.5 mm
Weight (packed)	5.5 kg
Weight (unpacked)	3.4 kg
Weight (Monitor only)	3.4 kg
Operating ambient temperature	5 - 35℃
Miscellaneous	
Miscellaneous	VESA DDC/ CI, Standardized mounting interface VESA FP MP MI 100 mm, Kensington lock
Color	Piano black
Package content	
Display delivered accessories	D-SUB Data cable 1.8 m , Audio cable 1.8 m, Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m, User manual, Warranty booklet, Quickstart flyer
Display delivered accessories notes	Data cables and audio cable detachable on display
Order information	
Order Code	S26361-K1381-V160
EAN-No.	4049699338809
Warranty	
Standard Warranty	3 years
Service level	Collect & Return Service
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Spare Parts availability	5 years
Service Weblink	http://www.fujitsu.com/fts/services/support



PC REVUE Editors Tip

PC REVUE Editors Tip, Fujitsu Display SL23T-1 LED, Test result: Best Buy, Slovakia - March 2012

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu SL23T-1 LED, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu SL23T-1 LED, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. http://www.fujitsu.com/fts/displays

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment/



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions Website: www.fujitsu.com/fts 2013-01-09 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms Copyright © Fujitsu Technology Solutions