


ARTronic® UPS

Line Interactive Uninterruptible Power Supply

ART 650 - 1200 - 2200 VA



- Microprocessor control guarantees high reliability.
- Equipped with Boost and Buck AVR.
- Green Power Function for energy saving.
- DC Start Function
- USB Port
- Auto restart while AC recovery.
- Compact size, Light Weight.
- Provides AC Overload protection.



Our work is power !



THE ART OF ELECTRONICS



ART 650 / 1200 / 2200 Technical Specifications

MODEL	ART 650	ART 1200	ART 2200
Capacity (VA / Watt)	650 VA / 360 W	1200 VA / 600 W	2200VA / 1100 W
Input			
Voltage	220 VAC	230 VAC	
Voltage Range	162 - 268 VAC	170 - 280 VAC	
Output			
Voltage	220 VAC	230 / 240 VAC	
Voltage Regulation (Batt Mode)	+ / - 10 %		
Frequency	50 Hz or 60 Hz		
Frequency Regulation (Batt Mode)	+ / - 1 Hz		
Output Waveform	Modified Sine Wave		
Battery			
Battery Type	12V / 7Ah x 1	12V / 7Ah x 2	12V / 9Ah x 2
Recharge Time	6 hours to 90% after complete discharge		
Transfer Time			
Typical	2-6 ms	4-8 ms	
Indicators & Control Panel			
AC Mode	Green lighting		
Battery Mode	Green lighting	Yellow Flashing	
Fault Mode	Red Flashing		
Audible Alarm			
Backup Mode	Sounding every 10 seconds		
Low Battery	Sounding every 1second		
Overload	Sounding every 0.5 second		
Fault	Continuously sounding		
Protections			
Full Protection	Discharge, overcharge, and overload protection		
Physical			
Dimension (mm), DXWXH	278(D) x 100(W) x 143(H)	365(D) x 139(W) x 195(H)	
Weight			
Net Weight	4.3 kgs	8.6 kgs	10.2 kgs
Environment			
Operating Environment	0°C - 40°C		
Noise Level	Less than 40dB		

*Product specifications are subject to change without further notice to third parties. © ARTronic Elektronik San. Müm. Tic. A.Ş.

ARTronic®

The art of electronics

Phone: +90 (216) 365 82 21 / Fax: +90 (216) 592 44 40

artronic@artronic.com.tr www.artronic.com.tr