



KTC W2221S5

54.6cm (21.5") LED Monitor



**Built-in Speakers
for BETTER
Multimedia EXPERIENCE.**

KTC[®]

Item	Value
Appearance	
Color	BLACK
Keys	RECALL, ASPECT, AUTO, +, -, MENU, POWER
Elevation adjustment	yes
Base Rotation	NO
Wall Hanger	75mm*75mm
Packaging Dimension with Base(W*H*D)	595*100*445mm
Unpackaging Dimension with Base(W*H*D)	535*36*394mm
Net Weight	5.0KG
Gross Weight	6.0KG
Packing Box Material	K5K B
Packing Box Bursting Strength	14kgf/cm ²
Packing Box Edgewise Crush	5500N/m
Polyfoam Material	EPS
Packing Bag Material	PE
Panel	
Panel Size	21.5
Aspect Ratio	16:09
Pixel Pitch	0.24825mm
Active Area	476.64*268.11mm ²
Best Resolution	1920*1080@60Hz
Max Brightness	300cd/m ²
Max Contrast	1000:01:00
Response Time(tr/ta)	5ms
Viewing Angle(LR/TB)	170/160
Display Color	16.7M
Performance	
H-Frequency	31KHz~68KHz
V-Frequency	56~63Hz
Power Supply	100V~240VAC 60/50Hz 1.0A
Power Consumption(Operating)	<30W on
Power Consumption(Suspend)	<1W flash in red color
Audio Power Consumption	3W +3W (option)
MTBF.	>15000h
Back Light life expectancy	>50000h
Interface	
VGA	15Pin D-Sub
DVI	DVI-D(option)
Audio in	3.5mm (option)
Safety	
withstand voltage strength	3000V 5s
Leakage Current	<3.5mA
Earth Resistance	<100mΩ
Environment	
Operating Temperature	5~40c
Storage Temperature	-20~55c
Operating Humidity	10%~85%
Storage Humidity	5%~95%
Atmospheric Pressure	86~104Kpa