




32" 12pt open frame touch monitor built into an eye catching slim bezel with high brightness

With 1920x1080 Full HD resolution and Projective Capacitive 12 point touch technology, the ProLite TF3222MC-B2 delivers seamless and accurate touch response. Featuring AMVA3 LED LCD screen technology, it offers exceptional colour performance and wide viewing angles, making it a perfect display for Interactive Digital Signage. The high brightness (500cd/m²) ensures crispy and clear images, resulting in outstanding information transmission performance, even in bright environments. In addition to the superb image quality, the screen comes with a rugged bezel, making it suitable for demanding environments. The open frame ProLite TF3222MC-B2 is the ideal solution for Interactive Digital Signage, Instore Retail, Kiosks, Gaming and Interactive Presentations.



AMVA3

AMVA3 technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter what angle you look at it.



Touch technology - Capacitive

This technology uses a sensor-grid of micro-fine wires integrated into the glass that covers the screen. Touch is detected because electrical characteristics of the sensor grid change when human finger is placed on the glass. Thanks to the glass overlay this technology is highly durable, and the touch function remains unaffected even if the glass is scratched. It offers perfect picture performance and will work with human finger (also latex gloved) and stylus-pen.

01 DISPLAY CHARACTERISTICS

Design	Open Frame
Diagonal	31.5", 80cm
Panel	AMVA3 Edge LED
Native resolution	1920 x 1080 (2.1 megapixel Full HD)
Aspect ratio	16:9
Brightness	500 cd/m ² typical
Brightness	425 cd/m ² with touch
Static contrast	3000:1 typical
Light transmittance	85%
Response time	8ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mln 8bit (6bit + Hi-FRC)
Horizontal Sync	31.47 - 67.5KHz
Vertical Sync	47 - 63Hz
Viewable area W x H	698.4 x 392.8mm, 27.5 x 15.5"
Pixel pitch	0.364mm
Bezel colour and finish	black, matte

02 TOUCH

Touch technology	projective capacitive
Touch points	12 (HID, only with supported OS)
Touch method	stylus, finger, glove (latex)
Touch interface	USB
Supported operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.

03 INTERFACES / CONNECTORS / CONTROLS

Analog signal input	VGA x1
Digital signal input	DVI x1

04 FEATURES

Max. non-stop operating time	20/7
Glass thickness	3mm
Glass hardness	7H
Impact testing	IP54 (front)
Housing (bezel)	metal
OSD key lock	yes

05 GENERAL

OSD languages	EN, DE, FR, ES, IT, RU, NL, PL
Control buttons	Menu, Scroll up/ Left, Scroll down/ Right, Return/ Exit/ Input, Power

User controls	picture (backlight, brightness, contrast, sharpness), display (auto adjustment, H. position, V. position, clock, phase), colour (temp, picture mode), advanced (aspect, image retention, OSD rotation, opening logo), input, other (reset, OSD time, OSD H. position, OSD V. position, language), information
---------------	---

Plug&Play	DDC2B
-----------	-------

06 MECHANICAL

Orientation	landscape, portrait
-------------	---------------------

VESA mounting	200 x 200mm
---------------	-------------

07 ACCESSORIES INCLUDED

Cables	power, VGA, USB
--------	-----------------

Guides	quick start guide, safety guide
--------	---------------------------------

08 POWER MANAGEMENT

Power supply unit	internal
-------------------	----------

Power supply	AC 100 - 240V, 50/60Hz
--------------	------------------------

Power usage	48W typical, 1.5W stand by
-------------	----------------------------


09 SUSTAINABILITY

Regulations	CB, CE, TÜV-Bauart, CU, cULus
-------------	-------------------------------

10 DIMENSIONS / WEIGHT

Product dimensions W x H x D	748.5 x 450 x 63mm
------------------------------	--------------------

Weight (without box)	12.8kg
----------------------	--------



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED