



## 27B3CA2

## High-performance clarity with 27" FHD monitor featuring 100Hz refresh rate and HDMI

Introducing the newest addition to the B3 line– a brilliant 27-inch display featuring an IPS panel for breathtaking visuals with 1920 x 1080 resolution and 100Hz refresh rates. If you're looking for a compact sized monitor but bigger than 23,8-inch , the 27B3CA2 is the ideal choice. Also, it provides USB-C which means it is possible to utilize video signals, power delivery and data transfer at the same time which will improve your productivity. Whether you're working or studying, enjoy a more comfortable and enjoyable viewing experience with the expansive screen size of the 27B3CA2.

| GENERAL        |            |
|----------------|------------|
| Model Name     | 27B3CA2    |
| Brand          | AOC        |
| Channel        | B2C        |
| Product type   | Monitor    |
| Product line   | Basic-line |
| Design family  | B3         |
| Classification | Hero       |

| OTHER INFORMATION |  |
|-------------------|--|
| EAN               | 4038986181471  |
| OSD languages     | English, Ukranian, Turkish, Polish, German, Portuguese, Spanish, French, Finnish, Korean, Japanese, Chinese (simplified), Chinese (traditional), Swedish, Dutch, Italian, Kroatian, Russian, Czech |
| Warranty period   | 3 years  |
| MTBF              | 30.000 hours (with backlight)  |

| DISPLAY INFORMATION              |                        |
|----------------------------------|------------------------|
| Screen size (inch)               | 27                     |
| Screen size (cm)                 | 68.58                  |
| Flat / Curved                    | Flat                   |
| Display viewing Area (HxW) in mm | 527,04 x 296,46        |
| Display hardness                 | 3Н                     |
| Panel treatment                  | Antiglare (AG)         |
| Pixel Pitch (mm)                 | 0.3114                 |
| Pixels per Inch                  | 82                     |
| Panel resolution                 | 1920×1080              |
| Resolution name                  | FHD                    |
| Aspect ratio                     | 16:9                   |
| Panel type                       | IPS                    |
| Backlight type                   | WLED                   |
| Max Refresh rate                 | 100 Hz                 |
| Response time GtG                | 4 ms                   |
| Response time MPRT               | 1 ms                   |
| Static contrast ratio            | 1300:1                 |
| Dynamic contrast ratio           | 20M:1                  |
| Viewing angle (CR10)             | 178/178                |
| Display colours                  | 16.7M (6bits+FRC)      |
| Brightness in nits               | 250 cd/m2              |
| OD Response (typical)            | 4 ms GtG               |
| Panel Haze Value                 | 25%                    |
| Support 1:1 function             | No                     |
| Panel PPI                        | 82 PPI (27"/1920x1080) |
| Local Dimming Zones              | Global Dimming         |

| VIDEO FEATURES                         |                |
|--|----------------|
| Sync technology (VRR)                  | Adaptive Sync  |
| Digital Signal Frequency Vertical      | 48-100Hz       |
| Digital Signal Frequency Horizontal    | 30k-115kHz     |
| HDR (High Dynamic Range)               | HDR Mode       |
| Blue Light Technology                  | Low Blue Light |
| Colour space (sRGB) CIE 1931 %         | 101.8          |
| Colour space (sRGB) CIE 1976 %         | 101.4          |
| Colour space (DCI-P3) CIE 1931 %       | 75             |
| Colour space (DCI-P3) CIE 1976 %       | 80.7           |
| Colour space (Adobe RGB) CIE 1931 %    | 75.4           |
| Colour space (Adobe RGB) CIE 1976<br>% | 86.9           |
| Colour space (NTSC) CIE 1931 %         | 72.1           |
| Colour space (NTSC) CIE 1976 %         | 88.4           |
| Colour space (BT 709) CIE 1931 %       | 101.8          |
| Colour space (BT 709) CIE 1976 %       | 101.4          |
| Colour space (BT 2020) CIE 1931 %      | 53.8           |
| Colour space (BT 2020) CIE 1976 %      | 58.8           |
| eyeSafe (TUV) hardware                 | No             |
| KVM                                    | No             |

| CABINET INFORMATION    |              |
|------------------------|--------------|
| Bezel type (front)     | Ultra Narrow |
| Light FX (RGB)         | No           |
| Speakers               | Yes          |
| Speaker power          | 2 W x 2      |
| Built-in Microphone    | No           |
| Kensington Lock        | Yes          |
| Vesa wallmount         | 100×100      |
| Quick release function | Yes          |
| Sound enhancement      | No           |
| VESA Mount screw Spec  | M4 x 10      |
| VESA Mount Support     | Yes          |

| ERGONOMIC INFORMATION |                          |
|-----------------------|--------------------------|
| Tilt                  | -5 (+3/-0) ~ +23 (-3/+0) |

| CONNECTIVITY INFORMATION              |  |
|---------------------------------------|--|
| HDMI                                  | HDMI 1.4 x 1   |
| Digital HDCP (HDMI version)           | HDCP 1.4   |
| USB-C connectivity                    | USB-C (DP Alt mode) x 1  |
| USB Hub                               | Yes  |
| USB Hub speed                         | USB 3.2 (Gen 1)  |
| USB downstream ports                  | 2  |
| USB fast charge port                  | Yes  |
| Audio Output                          | 1x Audio out combine with microphone   |
| Microphone in                         | Yes  |
| mini USB (for external keypad)        | No   |
| MST / Daisy chain (DP out or TBT out) | No   |
| Thunderbolt in                        | 0x   |
| Thunderbolt out                       | 0x   |
| PD for USB C/TBT                      | USB C1 : PD=65W, PD3.0, 5V/3A, 7V/3A, 9V/3A, 10V/3A, 12V/3A, 15V/3A, 20V/3.25A |
| USB Hub up stream                     | 1 x USB3.2 type C Gen 1, 5 Gbit/s  |
| Microphone out                        | No   |
| DVI                                   | 0x   |
| RJ45                                  | No   |

| POWER CONSUMPTION                       |                    |
|---|--------------------|
| Power supply                            | Internal           |
| Power source                            | 100 - 240V 50/60Hz |
| Power consumption on (maximum) in watts | 135                |
| Power consumption on (typical) in watts | 35                 |
| Power consumption standby in watts      | 0.5                |
| Power consumption off in watts          | 0.3                |

| PRODUCT DIMENSIONS                       |                       |
|--|-----------------------|
| Product dimensions incl. base (WxHxD) mm | 616.6 x 452.9 x 229.5 |
| Product dimensions excl. base (WxHxD) mm | 616.6 x 45.4x 356.7   |
| Packaging dimensions (WxHxD)<br>mm       | 690 x 142 x 453       |
| Packaging dimensions (WxHxD)<br>mm (CN)  | 690 x 142 x 453       |
| Gross weight incl. package (in kg)       | 4.43                  |
| Net weight excl. package (in kg)         | 6.93                  |
| Gross weight incl. package (in kg) (CN)  | 6.93                  |
| Product without stand (kg)               | 4.05                  |

| WHAT'S IN THE BOX |     |
|-------------------|-----|
| HDMI cable        | 1.5 |
| USB-C to C cable  | 1.8 |
| Power Cable       | Yes |
| Power adaptor     | No  |

| GAMING FEATURES |    |
|-----------------|----|
| Low Input Lag   | No |