HP Smart Tank 755 All-in-One (28B72A)



Specifications

| Print quality black (best) | Up to 1200 x 1200 rendered dpi |
|-----------------------------------|--|
| Print quality color (best) | Up to 4800×1200 optimized dpi color when printing from a computer and 1200 inp ut dpi |
| Print speed black (ISO, A4) | Up to 15 ppm |
| Print Speed Color (ISO) | Up to 9 ppm |
| Print speed | Print speed up to 15 ppm (black) and 9 ppm (color) |
| Functions | Print, Scan, Copy, ADF, Wireless |
| Duplex printing | Automatic |
| Duty cycle (monthly, A4) | Up to 5,000 pages |
| Duty cycle (monthly, letter) | Up to 5,000 pages |
| Printer smart software features | Duplex Printing |
| Energy savings feature technology | Schedule On and Schedule Off; HP Auto-Off Technology |
| Replacement cartridges | HP GT53 90-ml Black bottle (~4000 pages); HP 53XL 135-ml Black bottle (~6000 pages); HP GT52 70-ml Cyan bottle (~8000 pages); HP GT52 70-ml Magenta bottle (~8000 pages); HP GT52 70-ml Yellow bottle (~8000 pages). For more information about fill and yield see www.hp.com/go/learnaboutsupplies ^[6] |
| Connectivity, standard | Hi-Speed USB 2.0; Wi-Fi; Bluetooth LE; LAN |
| Network capabilities | Yes, via built-in Ethernet; Wi-Fi |
| Wireless capability | Yes, 2.4/5G dual band Wi-Fi, Wi-Fi Direct, Bluetooth low energy |
| Mobile printing capability | Apple AirPrint; Mopria certified; HP Print Service Plugin (Android printing); HP Smart app; Wi-Fi Direct Printing |
| Software included | HP Printer Software, available online |
| Compatible Operating Systems | Windows 10, 7; macOS v10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur; (Windows 10, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Internet Explorer; macOS v10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur; 2 GB HD; Internet required) |
| Sustainable impact specifications | 25% post-consumer recycled plastic; Recyclable through HP Planet Partners |
| Energy star certified | No |
| Blue Angel compliant | Yes, Blue Angel DE-UZ 219—only ensured when using Original HP supplies |
| Scan speed (normal, A4) | Up to 3 ppm (200 ppi, color); Up to 5 ppm (200 ppi, mono) |
| Scan speed (normal, letter) | Up to 3 ppm (200 ppi, color); Up to 5 ppm (200 ppi, mono) |
| Scan file format | BMP, JPEG, TIFF, PDF, PNG |
| Scan input modes | Front Panel Copy; HP Software; EWS |
| Scan technology | Contact Image Sensor (CIS) |
| | |

| Scanner type | Flatbed, ADF |
|--------------------------------|--|
| Display | Twisted Pneumatic Positive, Reflective, LCD 2 x 0.4 in (50.8 x 10.16 mm) |
| Minimum dimensions (W x D x H) | 42.75 x 36.40 x 24.03 cm |
| Minimum dimensions (W x D x H) | 16.83 x 14.33 x 9.46 in |
| Weight | 7.70 kg |
| Weight | 16.98 lb |
| Power consumption | 0.1 watts (off);1.10 watts (sleep) ^[2] |
| Power supply type | Internal |

Additional specifications

| Accessories | None |
|--|--|
| Acoustic power emissions (active copy) | 6.3 B(A) (copying at 9ppm with ADF running |
| Acoustic power emissions (active, printing) | 6.5 B(A) (printing at 10ppm) |
| Acoustic pressure emissions | 59.4 dB(A) (printing at 10ppm) |
| Automatic document feeder capacity | Standard, 35 sheets |
| Automatic paper sensor | Yes |
| Bit depth | 24-bit |
| Borderless printing | Yes (up to 8.5 x 11 in, 210 x 297 mm) |
| Bottom margin (A4) | 3.3 mm |
| Camera phone description | No |
| Camera phone supported | No |
| Color copy capability | Yes |
| Color scanning | Yes |
| Color(s) of printing supplies | Black; Cyan; Magenta; Yellow |
| Control panel | Power On/Off, ID copy, Color Copy, Black Copy, Wi-Fi, Info, Cancel and Resume button |
| Copier settings | Number of Copies, Resize, Quality, Lighter/Darker, Papersize, Papertype, ID Copy |
| Copies, maximum | Up to 99 copies |
| Copy reduce / enlarge settings | 25 to 400% |
| Copy resolution (black graphics) | Up to 600 dpi |
| Copy resolution (black text) | Up to 600 dpi |
| Copy resolution (color text and graphics) | Up to 600 x 600 dpi |
| Copy speed black (ISO) | Up to 13 cpm |
| Copy speed color (ISO) | Up to 6 cpm |
| Count of cartons per pallet layer | 8 |
| Count of layers in pallet | 6 |
| Country of origin | Made in China |
| Dimensions with trays up (W \times D \times H) | 427.54 x 364.00 x 240.25 mm |
| | |

| Electromagnetic compatibility | CISPR 32:2015/EN 55032:2015+A11:2020 Class B; CISPR24:2010+A1:2015/EN 55024:2010+A1:2015; EN55035:2017+A11:2020/CISPR35:2016; EN 61000-3-2:2019; EN 61000-3-3:2013+A1:2019; FCC CFR 47 Part 15 Subpart B; ICES-003 Issue 7:2020; EN 301 489-1 V2.2.3; EN 301 489-17 V3.2.2 |
|---------------------------------------|---|
| Enhanced scanning resolution | Up to 1200 dpi |
| Envelope Feeder | No |
| Exifprint supported | No |
| File Format Supported | PDF; BMP; PNG; TIF; JPG |
| First page out black (A4, ready) | As fast as 14 sec |
| First page out color (A4, ready) | As fast as 16 sec |
| First page out footnote | For details see http://www.hp.com/go/printerclaims |
| Geographic availability | CN, LA EM |
| Ink types | Pigment-based (black); Dye-based (color) |
| Input capacity | Up to 250 sheets |
| Left margin (A4) | 3.3 mm |
| Levels of grayscale | 256 |
| Mac compatible | Yes |
| Maximum Input Capacity (envelopes) | Up to 30 envelopes |
| Maximum Memory | 256 MB |
| Maximum dimensions (W x D x H) | 17.86 x 17.35 x 9.83 in |
| Maximum dimensions (W x D x H) | 453.55 x 440.73 x 249.63 mm |
| Maximum input capacity (cards) | Up to 30 cards |
| Maximum input capacity (labels) | Up to 20 sheets |
| Maximum input capacity (photo paper) | Up to 50 sheets |
| Maximum input capacity (sheets) | Up to 250 sheets |
| Maximum output capacity (cards) | Up to 30 cards |
| Maximum output capacity (envelopes) | Up to 30 envelopes |
| Maximum output capacity (labels) | Up to 20 sheets |
| Maximum output capacity (photo paper) | Up to 30 sheets |
| Maximum output capacity (sheets) | Up to 100 sheets |
| Maximum print area | 215.9 x 355.6 mm |
| Media sizes supported | Letter; Legal; Government Legal; Executive; Statement; 4×6 in; 5×7 in; 8×10 in; L; Photo 2L; Envelope(#10, Monarch, 5.5 bar); Card $(4 \times 6$ in, 5×8 in) |

| Media sizes supported | A4; A5; A6; B5 (JIS); Envelope (DL, C5, C6, Chou #3, Chou #4); Card (Hagaki, Ofuku Hagaki) |
|--|---|
| Media sizes supported, key | 10 x 15 cm; A4; Envelopes |
| Media sizes supported, key | Envelopes; Legal; Letter; 4 x 6 in |
| Media sizes, custom | 88.9 x 127 mm to 215.9 x 355.6 mm |
| Media sizes, custom | 3.5 x 5 in to 8.5 x 14 in |
| Media types | Plain Paper, HP Photo Papers, HP Matte Brochure or Professional Paper, HP Matte Presentation Paper, HP Glossy Brochure or Professional Paper, Other Photo Inkjet Papers, Other Matte Inkjet Papers, Other Glossy Inkjet Papers, Plain Paper, Light/Recycled |
| Media weight, recommended | 60 to 105 g/m² |
| Media weight, recommended | 16 to 28 lb |
| Media weight, supported | Plain paper: 16 to 28 lb; Envelopes: 20 to 24 lb; Cards: up to 110 lb; Photo paper: up to 66 lb |
| Media weight, supported | Plain paper: 60 to 105 g/m²; Envelopes: 75 to 90 g/m²; Cards: up to 200 g/m²; Photo paper: up to 250 g/m² |
| Memory | 256 MB |
| Minimum System Requirements | Windows 10, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Internet Explorer. |
| Minimum System Requirements for Macintosh | macOS v10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur; 2 GB HD; Internet required |
| | |
| Multitasking supported | No |
| Multitasking supported Non-Operating Humidity Range | No 5 to 90% RH (non-condensing) |
| | |
| Non-Operating Humidity Range | 5 to 90% RH (non-condensing) |
| Non-Operating Humidity Range Number of print cartridges | 5 to 90% RH (non-condensing) 4 (1 each black bottle, set of 3 color bottles) |
| Non-Operating Humidity Range Number of print cartridges Number of users | 5 to 90% RH (non-condensing) 4 (1 each black bottle, set of 3 color bottles) 1-3 Users |
| Non-Operating Humidity Range Number of print cartridges Number of users Operating altitude | 5 to 90% RH (non-condensing) 4 (1 each black bottle, set of 3 color bottles) 1-3 Users Up to 10,000 ft |
| Non-Operating Humidity Range Number of print cartridges Number of users Operating altitude Operating humidity range | 5 to 90% RH (non-condensing) 4 (1 each black bottle, set of 3 color bottles) 1-3 Users Up to 10,000 ft 15 to 80% RH (non-condensing) |
| Non-Operating Humidity Range Number of print cartridges Number of users Operating altitude Operating humidity range Operating temperature range | 5 to 90% RH (non-condensing) 4 (1 each black bottle, set of 3 color bottles) 1-3 Users Up to 10,000 ft 15 to 80% RH (non-condensing) 5 to 40°C |
| Non-Operating Humidity Range Number of print cartridges Number of users Operating altitude Operating humidity range Operating temperature range Operating temperature range | 5 to 90% RH (non-condensing) 4 (1 each black bottle, set of 3 color bottles) 1-3 Users Up to 10,000 ft 15 to 80% RH (non-condensing) 5 to 40°C 41 to 104°F HP GT53 90-ml Black Original Ink Bottle 1VV22AE, HP GT53XL 135-ml Black Original Ink Bottle 1VV21AE, HP GT52 Cyan Original Ink Bottle MOH54AE, HP GT52 Magenta Original Ink Bottle MOH55AE, HP GT52 Yellow Original Ink Bottle MOH56AE, HP GT53 90-ml Black Original Ink Bottle 1VV22AL, HP GT52 Cyan Original Ink Bottle MOH54AL, HP GT52 Magenta Original Ink Bottle MOH55AL, HP GT52 Yellow Original Ink Bottle MOH56AL, HP GT52 Nagenta Original Ink Bottle MOH55AL, HP GT52 Yellow Original Ink Bottle MOH56AL, HP GT53 90-ml Black Original Ink Bottle MOH56AL, HP GT53 90-ml Black Original Ink Bottle 1VV22AA, HP GT53XL 135-ml Black Original Ink Bottle 1VV21AA, HP GT52 Cyan Original Ink Bottle MOH54AA, HP GT52 Magenta Original Ink Bottle |
| Non-Operating Humidity Range Number of print cartridges Number of users Operating altitude Operating humidity range Operating temperature range Operating temperature range Orderable supplies | 5 to 90% RH (non-condensing) 4 (1 each black bottle, set of 3 color bottles) 1-3 Users Up to 10,000 ft 15 to 80% RH (non-condensing) 5 to 40°C 41 to 104°F HP GT53 90-ml Black Original Ink Bottle 1VV22AE, HP GT53XL 135-ml Black Original Ink Bottle 1VV21AE, HP GT52 Cyan Original Ink Bottle MOH54AE, HP GT52 Magenta Original Ink Bottle MOH55AE, HP GT52 Yellow Original Ink Bottle MOH56AE, HP GT53 90-ml Black Original Ink Bottle 1VV22AL, HP GT52 Cyan Original Ink Bottle MOH54AL, HP GT52 Magenta Original Ink Bottle MOH55AL, HP GT52 Yellow Original Ink Bottle MOH55AL, HP GT52 Yellow Original Ink Bottle MOH55AL, HP GT52 Yellow Original Ink Bottle MOH56AL, HP GT52 3-pack Cyan/Magenta/Yellow Original Ink Bottles X4E44AL, HP GT53 90-ml Black Original Ink Bottle 1VV22AA, HP GT53XL 135-ml Black Original Ink Bottle 1VV21AA, HP GT52 Cyan Original Ink Bottle MOH54AA, HP GT52 Magenta Original Ink Bottle MOH55AA, HP GT52 Yellow Original Ink Bottle MOH55AA |
| Non-Operating Humidity Range Number of print cartridges Number of users Operating altitude Operating humidity range Operating temperature range Operating temperature range Orderable supplies Output capacity | 5 to 90% RH (non-condensing) 4 (1 each black bottle, set of 3 color bottles) 1-3 Users Up to 10,000 ft 15 to 80% RH (non-condensing) 5 to 40°C 41 to 104°F HP GT53 90-ml Black Original Ink Bottle 1VV22AE, HP GT53XL 135-ml Black Original Ink Bottle 1VV21AE, HP GT52 Cyan Original Ink Bottle MOH54AE, HP GT52 Magenta Original Ink Bottle MOH55AE, HP GT52 Yellow Original Ink Bottle MOH56AE, HP GT51XL 135-ml Black Original Ink Bottle X4E40AE, HP GT53 90-ml Black Original Ink Bottle 1VV22AL, HP GT52 Cyan Original Ink Bottle MOH55AL, HP GT52 Yellow Original Ink Bottle MOH56AL, HP GT52 Magenta Original Ink Bottle MOH55AL, HP GT52 Yellow Original Ink Bottle MOH56AL, HP GT52 3-pack Cyan/Magenta/Yellow Original Ink Bottle S4E44AL, HP GT53 90-ml Black Original Ink Bottle 1VV22AA, HP GT53XL 135-ml Black Original Ink Bottle 1VV21AA, HP GT52 Cyan Original Ink Bottle MOH55AA, HP GT52 Yellow Original Ink Bottle MOH55AA, HP GT52 Yellow Original Ink Bottle MOH55AA, HP GT52 Yellow Original Ink Bottle MOH56AA Up to 100 sheets |

| Package weight 23.54 lb Pallet dimensions 48 x 40 x 102 in Pallet dimensions (W x D x H) 1220 x 1016 x 2590 mm Pallet weight 942 lb Pallet weight 428 kg Paper handling input, standard 250-sheet input tray Paper handling output, standard 100-sheet output tray Paper trays, maximum 1 Paper trays, standard 1 Photo proofsheets supported No PictBridge description No PictBridge supported No Power Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz) Print Technology Ink Print colors Yes Print colors Yes Print tendosy Ink Print head nozzles 704 (Black), 588 (Tri-color) Print languages HP PCL 3 GUI Print speed black (GSO) Up to 15 ppm Print speed color (GSO) Up to 23 ppm Print speed color (GSO) Up to 22 ppm Print rechnology HP Thermal Inkjet Print rechnology HP Thermal Inkjet <th>Package dimensions (W x D x H)</th> <th>19.06 x 11.18 x 16.14 in</th> | Package dimensions (W x D x H) | 19.06 x 11.18 x 16.14 in |
|--|---------------------------------|---|
| Pallet dimensions | Package weight | 23.54 lb |
| Pallet dimensions (W x D x H) Pallet weight Pallet weight Paper handling input, standard Paper handling output, standard Paper trays, maximum Paper trays, standard Photo proofsheets supported No PictBridge description No PictBridge description No Power Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz) Print Technology Ink Print colors Yes Print colors with languages Print speed black (Graft, A4) Print speed black (Graft, A4) Print speed color (Graft, A4) Print technology Print | Package weight | 10.70 kg |
| Pallet weight 942 lb Pallet weight 428 kg Paper handling input, standard 250-sheet input tray Paper handling output, standard 100-sheet output tray Paper trays, maximum 1 Paper trays, standard 1 Photo proofsheets supported No PittBridge description No PittBridge supported No Power Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz) Print Technology Ink Print Technology Ves Print colors Wes Print colors maximum 4 Print head nozzles 704 (Black), 588 (Tri-color) Print languages HP CL 3 GUI Print speed black (Graft, A4) Up to 23 ppm Print speed black (draft, A4) Up to 23 ppm Print speed color (Graft, A4) Up to 22 ppm Print speed color (draft, A4) Up to 22 ppm Print rechnology HP Thermal Inkjet Printer drivers included HP PCL 3 GUI Processor speed 800 MHz Product logos USB High-Speed Certified Registered Trademark Logo; PAP20; EPEAT Silver Product name (back) HP Smart Tank 750 series Product name (front) HP Smart Tank 750 series Product name (front) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series | Pallet dimensions | 48 x 40 x 102 in |
| Pallet weight 428 kg Paper handling input, standard 250-sheet input tray Paper handling output, standard 100-sheet output tray Paper trays, maximum 1 Paper trays, standard 1 Photo proofsheets supported No PictBridge description No PictBridge supported No Power Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz) Print Technology Ink Print colors Yes Print colors Yes Print colors maximum 4 Print head nozzles 704 (Black), 588 (Tri-color) Print heads 2 (1 each black, tri-color) Print speed black (ISO) Up to 15 ppm Print speed black (ISO) Up to 23 ppm Print speed color (ISO) Up to 29 ppm Print speed color (ISO) USB High-Speed Certified Registered Trademark Logo: PAP20; EPEAT Silver Product name (back) HP Smart Tank 750 series Product name (front) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Quantity per pallet 48 | Pallet dimensions (W x D x H) | 1220 x 1016 x 2590 mm |
| Paper handling input, standard Paper trays, maximum 100-sheet output tray Paper trays, maximum 1 Paper trays, standard Photo proofsheets supported No PictBridge description No PictBridge supported No Power Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz) Print Technology Ink Print Technology Print colors Yes Print colors maximum 4 Print head nozzles 704 (Black), 588 (Tri-color) Print languages HP PCL 3 GUI Print speed black (ISD) Up to 15 ppm Print speed black (draft, A4) Up to 23 ppm Print speed color (ISO) Print speed color (ISO) Up to 9 ppm Print speed color (ISO) Print speed color (ISO) HP Thermal Inkjet Processor speed 800 MHz Product logos USB High-Speed Certified Registered Trademark Logo; PAP20; EPEAT Silver Product name (back) HP Smart Tank 750 series Product name (primary) HP Smart Tank 750 series Product name (primary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series | Pallet weight | 942 lb |
| Paper handling output, standard Paper trays, maximum 1 Paper trays, standard 1 Photo proofsheets supported No PictBridge description No PictBridge supported No Power Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz) Print Technology Ink Print colors Yes Print colors maximum 4 Print head nozzles 704 (Black), 588 (Tri-color) Print tanguages Print speed black (ISO) Up to 15 ppm Print speed black (IsO) Up to 23 ppm Print speed color (IsO) Print speed color (IsO) Print speed color (IsO) Print echnology HP Thermal Inkjet Print er drivers included HP PCL 3 GUI Processor speed 800 MHz Product name (back) HP Smart Tank 750 series Product name (primary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Quantity per pallet 48 | Pallet weight | 428 kg |
| Paper trays, maximum Paper trays, standard Photo proofsheets supported No PictBridge description No PictBridge supported No Power Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz) Print Technology Ink Print colors Yes Print colors Print head nozzles 704 (Black), 588 (Tri-color) Print heads 2 (1 each black, tri-color) Print speed black (ISO) Up to 15 ppm Print speed black (ISO) Up to 23 ppm Print speed black (draft, A4) Up to 23 ppm Print speed color (ISO) Up to 9 ppm Print speed color (ISO) Print technology HP Thermal Inkjet Printer drivers included HP PCL 3 GUI Processor speed 800 MHz Product name (back) HP Smart Tank 750 series Product name (primary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series | Paper handling input, standard | 250-sheet input tray |
| Paper trays, standard Photo proofsheets supported No PictBridge description No PictBridge supported No Power Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz) Print Technology Ink Print colors Yes Print colors maximum 4 Print head nozzles 704 (Black), 588 (Tri-color) Print languages HP PCL 3 GUI Print speed black (ISO) Up to 15 ppm Print speed black (ISO) Up to 23 ppm Print speed color (ISO) Up to 9 ppm Print speed color (ISO) Up to 22 ppm Print technology HP PCL 3 GUI Print edrivers included HP PCL 3 GUI Processor speed 800 MHz Product name (back) HP Smart Tank 750 series Product name (front) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Product name (secondary) Quantity per pallet 48 | Paper handling output, standard | 100-sheet output tray |
| Photo proofsheets supported PictBridge description No PictBridge supported No Power Input voltage: 100 to 240 VAC (*/- 10%), 50/60 Hz (*/- 3 Hz) Print Technology Ink Print colors Yes Print colors waximum 4 Print head nozzles 704 (Black), 588 (Tri-color) Print languages Print speed black (ISO) Up to 15 ppm Print speed black (ISO) Up to 23 ppm Print speed color (ISO) Up to 9 ppm Print speed color (ISO) Up to 22 ppm Print speed color (IsO) Print technology HP Thermal Inkjet Printer drivers included HP PCL 3 GUI Processor speed 800 MHz Product name (back) HP Smart Tank 750 series Product name (grimary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series | Paper trays, maximum | 1 |
| PictBridge description PictBridge supported No Power Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz) Print Technology Ink Print colors Yes Print colors Yes Print colors maximum 4 Print head nozzles 704 (Black), 588 (Tri-color) Print heads 2 (1 each black, tri-color) Print languages HP PCL 3 GUI Print speed black (ISO) Up to 15 ppm Print speed black (ISO) Up to 9 ppm Print speed color (ISO) Up to 9 ppm Print speed color (ISO) Up to 22 ppm Print technology HP Thermal Inkjet Printer drivers included HP PCL 3 GUI Processor speed 800 MHz Product logos USB High-Speed Certified Registered Trademark Logo; PAP20; EPEAT Silver Product name (back) HP Smart Tank 750 series Product name (primary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series | Paper trays, standard | 1 |
| PictBridge supported Power Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz) Print Technology Ink Print colors Yes Print colors maximum 4 Print head nozzles 704 (Black), 588 (Tri-color) Print heads 2 (1 each black, tri-color) Print languages HP PCL 3 GUI Print speed black (ISO) Up to 15 ppm Print speed black (draft, A4) Up to 23 ppm Print speed color (ISO) Up to 9 ppm Print speed color (draft, A4) Up to 22 ppm Print technology HP Thermal Inkjet Printer drivers included HP PCL 3 GUI Processor speed 800 MHz Product logos USB High-Speed Certified Registered Trademark Logo; PAP20; EPEAT Silver Product name (back) HP Smart Tank 750 series Product name (grimary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series | Photo proofsheets supported | No |
| Power Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz) Print Technology Ink Print colors Yes Print colors maximum 4 Print head nozzles 704 (Black), 588 (Tri-color) Print heads 2 (1 each black, tri-color) Print languages HP PCL 3 GUI Print speed black (ISO) Up to 15 ppm Print speed black (ISO) Up to 23 ppm Print speed color (ISO) Up to 9 ppm Print speed color (IsO) Up to 22 ppm Print technology HP Thermal Inkjet Printer drivers included HP PCL 3 GUI Processor speed 800 MHz Product logos USB High-Speed Certified Registered Trademark Logo; PAP20; EPEAT Silver Product name (back) HP Smart Tank 750 series Product name (front) HP Smart Tank 750 series Product name (grimary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series | PictBridge description | No |
| Print Technology Print colors Yes Print colors maximum 4 Print head nozzles 704 (Black), 588 (Tri-color) Print heads 2 (1 each black, tri-color) Print languages HP PCL 3 GUI Print speed black (ISO) Up to 15 ppm Print speed black (draft, A4) Up to 23 ppm Print speed color (ISO) Up to 9 ppm Print speed color (ISO) Up to 22 ppm Print technology HP Thermal Inkjet Printer drivers included HP PCL 3 GUI Processor speed 800 MHz Product logos USB High-Speed Certified Registered Trademark Logo; PAP20; EPEAT Silver Product name (back) HP Smart Tank 750 series Product name (primary) HP Smart Tank 750 series Product name (primary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series | PictBridge supported | No |
| Print colors Maximum 4 Print head nozzles 704 (Black), 588 (Tri-color) Print heads 2 (1 each black, tri-color) Print languages HP PCL 3 GUI Print speed black (ISO) Up to 15 ppm Print speed black (draft, A4) Up to 23 ppm Print speed color (ISO) Up to 9 ppm Print speed color (ISO) Up to 22 ppm Print technology HP Thermal Inkjet Printer drivers included HP PCL 3 GUI Processor speed 800 MHz Product logos USB High-Speed Certified Registered Trademark Logo; PAP20; EPEAT Silver Product name (back) HP Smart Tank 750 series Product name (primary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series | Power | Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz) |
| Print colors maximum Print head nozzles 704 (Black), 588 (Tri-color) Print heads 2 (1 each black, tri-color) Print languages HP PCL 3 GUI Print speed black (ISO) Up to 15 ppm Print speed black (draft, A4) Up to 23 ppm Print speed color (ISO) Up to 9 ppm Print speed color (draft, A4) Up to 22 ppm Print technology HP Thermal Inkjet Printer drivers included HP PCL 3 GUI Processor speed 800 MHz Product logos USB High-Speed Certified Registered Trademark Logo; PAP20; EPEAT Silver Product name (back) HP Smart Tank 750 series Product name (front) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series | Print Technology | Ink |
| Print head nozzles 704 (Black), 588 (Tri-color) Print heads 2 (1 each black, tri-color) Print languages HP PCL 3 GUI Print speed black (ISO) Up to 15 ppm Print speed black (draft, A4) Up to 23 ppm Print speed color (ISO) Up to 9 ppm Print speed color (ISO) Up to 22 ppm Print technology HP Thermal Inkjet Printer drivers included HP PCL 3 GUI Processor speed 800 MHz Product logos USB High-Speed Certified Registered Trademark Logo; PAP20; EPEAT Silver Product name (back) HP Smart Tank 750 series Product name (primary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series | Print colors | Yes |
| Print heads 2 (1 each black, tri-color) Print languages HP PCL 3 GUI Print speed black (ISO) Up to 15 ppm Print speed black (draft, A4) Up to 23 ppm Print speed color (ISO) Up to 9 ppm Print speed color (draft, A4) Up to 22 ppm Print technology HP Thermal Inkjet Printer drivers included HP PCL 3 GUI Processor speed 800 MHz Product logos USB High-Speed Certified Registered Trademark Logo; PAP2O; EPEAT Silver Product name (back) HP Smart Tank 750 series Product name (front) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series | Print colors maximum | 4 |
| Print languages HP PCL 3 GUI Print speed black (ISO) Up to 15 ppm Print speed black (draft, A4) Up to 23 ppm Print speed color (ISO) Up to 9 ppm Print speed color (draft, A4) Up to 22 ppm Print technology HP Thermal Inkjet Printer drivers included HP PCL 3 GUI Processor speed 800 MHz Product logos USB High-Speed Certified Registered Trademark Logo; PAP20; EPEAT Silver Product name (back) HP Smart Tank 750 series Product name (front) HP Smart Tank 750 series Product name (primary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Quantity per pallet 48 | Print head nozzles | 704 (Black), 588 (Tri-color) |
| Print speed black (ISO) Print speed black (draft, A4) Up to 23 ppm Print speed color (ISO) Up to 9 ppm Print speed color (draft, A4) Up to 22 ppm Print technology HP Thermal Inkjet Printer drivers included HP PCL 3 GUI Processor speed 800 MHz Product logos USB High-Speed Certified Registered Trademark Logo; PAP20; EPEAT Silver Product name (back) HP Smart Tank 750 series Product name (front) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series A8 | Print heads | 2 (1 each black, tri-color) |
| Print speed color (ISO) Up to 9 ppm Print speed color (IsO) Up to 9 ppm Print speed color (draft, A4) Up to 22 ppm Print technology HP Thermal Inkjet Printer drivers included HP PCL 3 GUI Processor speed 800 MHz Product logos USB High-Speed Certified Registered Trademark Logo; PAP20; EPEAT Silver Product name (back) HP Smart Tank 750 series Product name (front) HP Smart Tank 750 series Product name (primary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Product name (secondary) 48 | Print languages | HP PCL 3 GUI |
| Print speed color (ISO) Print speed color (draft, A4) Up to 22 ppm Print technology HP Thermal Inkjet Printer drivers included HP PCL 3 GUI Processor speed 800 MHz Product logos USB High-Speed Certified Registered Trademark Logo; PAP20; EPEAT Silver Product name (back) HP Smart Tank 750 series Product name (front) HP Smart Tank 750 series Product name (primary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series | Print speed black (ISO) | Up to 15 ppm |
| Print speed color (draft, A4) Print technology HP Thermal Inkjet HP PCL 3 GUI Processor speed 800 MHz Product logos USB High-Speed Certified Registered Trademark Logo; PAP20; EPEAT Silver Product name (back) HP Smart Tank 750 series Product name (front) HP Smart Tank 750 series Product name (primary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series 48 | Print speed black (draft, A4) | Up to 23 ppm |
| Printer drivers included HP PCL 3 GUI Processor speed 800 MHz Product logos USB High-Speed Certified Registered Trademark Logo; PAP20; EPEAT Silver Product name (back) HP Smart Tank 750 series Product name (front) HP Smart Tank 750 series Product name (primary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Quantity per pallet 48 | Print speed color (ISO) | Up to 9 ppm |
| Printer drivers included HP PCL 3 GUI Processor speed 800 MHz Product logos USB High-Speed Certified Registered Trademark Logo; PAP20; EPEAT Silver Product name (back) HP Smart Tank 750 series Product name (front) HP Smart Tank 750 series Product name (primary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Quantity per pallet 48 | Print speed color (draft, A4) | Up to 22 ppm |
| Processor speed800 MHzProduct logosUSB High-Speed Certified Registered Trademark Logo; PAP20; EPEAT SilverProduct name (back)HP Smart Tank 750 seriesProduct name (front)HP Smart Tank 750 seriesProduct name (primary)HP Smart Tank 750 seriesProduct name (secondary)HP Smart Tank 750 seriesQuantity per pallet48 | Print technology | HP Thermal Inkjet |
| Product logos USB High-Speed Certified Registered Trademark Logo; PAP20; EPEAT Silver Product name (back) HP Smart Tank 750 series HP Smart Tank 750 series Product name (primary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Quantity per pallet 48 | Printer drivers included | HP PCL 3 GUI |
| Product name (back) HP Smart Tank 750 series Product name (front) HP Smart Tank 750 series Product name (primary) HP Smart Tank 750 series Product name (secondary) HP Smart Tank 750 series Quantity per pallet 48 | Processor speed | 800 MHz |
| Product name (front)HP Smart Tank 750 seriesProduct name (primary)HP Smart Tank 750 seriesProduct name (secondary)HP Smart Tank 750 seriesQuantity per pallet48 | Product logos | USB High-Speed Certified Registered Trademark Logo; PAP20; EPEAT Silver |
| Product name (primary)HP Smart Tank 750 seriesProduct name (secondary)HP Smart Tank 750 seriesQuantity per pallet48 | Product name (back) | HP Smart Tank 750 series |
| Product name (secondary) HP Smart Tank 750 series Quantity per pallet 48 | Product name (front) | HP Smart Tank 750 series |
| Quantity per pallet 48 | Product name (primary) | HP Smart Tank 750 series |
| | Product name (secondary) | HP Smart Tank 750 series |
| RMN number SNPRC-2102-03 | Quantity per pallet | 48 |
| | RMN number | SNPRC-2102-03 |

| Recommended Macintosh system requirements | macOS v10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur; 2 GB HD; Internet required |
|---|---|
| Recommended monthly page volume | 400 to 800 |
| Recommended monthly page volume note | HP recommends that the number of pages per month of imaged output be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period. |
| Recommended operating humidity range | 20 to 80% RH |
| Recommended operating temperature range | 15 to 30°C |
| Recommended operating temperature range | 59 to 86°F |
| Right margin (A4) | 3.3 mm |
| Safety | IEC 60950-1 & IEC 62368-1 Ed. 2 compliant; Safety CSA NRTL; EU RED and EN 62368-1 Ed. 2 compliant; NEMKO GS approved; Mexico NOM-1-NYCE, Singapore "Safety Mark"; Russia EAC; China CCC |
| Scan resolution, hardware | Up to 1200 x 1200 dpi |
| Scan resolution, optical | Up to 1200 dpi |
| Scan size (ADF), maximum | 8.5 x 14 in |
| Scan size (ADF), maximum | 216 x 356 mm |
| Scan size, maximum | 216 x 297 mm |
| Scan size, maximum | 8.5 x 11.69 in |
| Scanning options (ADF) | Single-sided |
| Send to email capability | Yes |
| Service & support features | With services, software, solutions and support from HP Total Care, you can use, protect and enjoy your HP technology; one-year technical support; one-year or 30,000 pages limited hardware warranty, whichever is earlier from the date of purchase; user replaceable parts have separate warranty periods; access to 24/7 world-class support services through http://www.hp.com/support; to improve your product experience, please take the time to register at http://www.register.hp.com. |
| Service & support options | Protect your investment—HP Total Care offers a variety of extended warranties and services, go to http://www.hp.com/support |
| Standard input capacity (cards) | Up to 30 cards |
| Standard input capacity (legal) | Up to 250 sheets |
| Standard media sizes (duplex) | A4; B5; Not supported for borderless photo |
| Standard media sizes (duplex, imperial) | Letter; Executive; Not supported for borderless photo |
| Standard memory note | Not upgradeable |
| Standard output capacity (cards) | Up to 30 cards |

| Standard output capacity (envelopes) | Up to 30 envelopes |
|--|--|
| Standard output capacity (labels) | Up to 20 sheets |
| Standard output capacity (legal) | Up to 50 sheets |
| Storage altitude | 15,000 ft |
| Storage temperature range | -40 to 60°C |
| Storage temperature range | -40 to 140°F |
| Sub-brand name | Smart Tank |
| System requirements, recommended | Windows 10, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Internet Explorer. |
| Target user and print volume | For teams up to 3 users; Prints up to 800 pages/month |
| Tariff numbers | National HTS: 8443310000; EU/AM Base HTS:8443310000; AP Base HTS: 84433111 |
| Telecom compliance (fax capability) | EN 300 328 V2.2.2; EN 301 893 V2.1.1; EN 300 440 V2.1.1 |
| Top key features | 35-sheet ADF; Scan to PDF; Two-sided printing |
| Top margin (A4) | 3.3 mm |
| Twain version | Version 2.1 |
| Typical electricity consumption (TEC) number | 0.20 kWh/Week |
| UNSPSC code | 43212104 |
| Vertical alignment accuracy | +/- 0.02 mm |
| Vertical alignment accuracy | +/- 0.0008 in |
| Video action printing supported | No |
| Wireless technologies | Bluetooth® 5.0; 802.11a/b/g/n/ac; Wi-Fi® |

^[2] Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty.

^[6] Average based on ISO/IEC 24711 or HP testing methodology and continuous printing. Actual yield varies considerably based on content of printed pages and other factors. For details see http://hp.com/go/learnaboutsupplies

Ink/Toner/Paper/Printer Supplies

Ink Supplies ★: Recommended

HP Ink Bottles

| HP 31 70-ml Cyan Original Ink Bottle | 1VU26AE |
|--|---------|
| HP 31 70-ml Magenta Original Ink Bottle | 1VU27AE |
| HP 31 70-ml Yellow Original Ink Bottle | 1VU28AE |
| HP 32XL 135-ml Black Original Ink Bottle | 1VV24AA |
| HP 32XL 135-ml Black Original Ink Bottle | 1VV24AE |
| HP GT52 Cyan Original Ink Bottle | MOH54AE |
| HP GT52 Magenta Original Ink Bottle | MOH55AE |
| HP GT52 Yellow Original Ink Bottle | MOH56AE |
| HP GT53 90-ml Black Original Ink Bottle | 1VV22AA |
| HP GT53 90-ml Black Original Ink Bottle | 1VV22AL |
| HP GT53XL 135-ml Black Original Ink Bottle | 1VV21AA |
| HP GT53XL 135-ml Black Original Ink Bottle | 1VV21AE |
| HP GT53XL 135-ml Black Original Ink Bottle | 1VV21AL |

HP Inkjet Printer Cartridges and Ink Supplies

| HP 6ZA17AE Black Printhead | 6ZA17AE |
|--|---------|
| HP 6ZA18AE Tri-color Printhead | 6ZA18AE |
| HP M0H50A Tri-color Replacement GT Printhead | MOH50AA |
| HP M0H50A Tri-color Replacement GT Printhead | M0H50AL |
| HP M0H51A Black Replacement GT Printhead | MOH51AA |
| HP M0H51A Black Replacement GT Printhead | M0H51AL |
| HP X4E75A Black Inktank Printhead | X4E75AL |

HP Paper Designed for Inkjet Printers

HP Inkjet Photo Paper

| HP Advanced Glossy Photo Paper-25 sht/4 x 6 in borderless | 3AG54A |
|---|--------|
| HP Advanced Glossy Photo Paper-25 sht/5 x 7 in | 3AG55A |
| HP Matte Photo Paper-25 sht/10 x 15 cm | 7HF70A |
| HP Matte Photo Paper-25 sht/4 x 6 in | 6QH46A |

HP Inkjet Brochure Paper

Disclaimer — Copyright

© Copyright 2021 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Generated by Dynamic Collateral Tool – (ww-en) – Oct 12, 2021 3:39 PM UTC+0000