



APC BACK-UPS HS 500VA 230V
Part Number: BH500INET

Output

Output Power Capacity

300 Watts / 500 VA

Max Configurable Power

300 Watts / 500 VA

Nominal Output Voltage

230V

Output Connections

(4) IEC 320 C13 (Battery Backup)



Input

Nominal Input Voltage

230V

Input Frequency

47 - 63 Hz

Input Connections

IEC-320 C14

Cord Length

2.44 meters

Batteries & Runtime

Battery Type

Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof

Typical recharge time

8 hour(s)

Replacement battery cartridge

[CURK2](#), [RBC2](#), [RBC2J](#)

RBC™ Quantity

1

Typical Backup Time
at Half Load

16.3 minutes (150 Watts)

Typical Backup Time
at Full Load

4.4 minutes (300 Watts)

Runtime Chart

[Back-UPS HS](#)

Communications & Management

Control panel

LED status display with On Line : On Battery : Replace Battery and Building Wiring Fault,Network link status LED

Audible Alarm

Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating

600 Joules

Dataline protection

RJ-11 Modem/Fax protection,RJ45 10/100 Base-T Ethernet protection,Co-axial Video / Cable protection

Physical

Maximum Height

372.00 mm

Maximum Width

225.00 mm

Maximum depth

105.00 mm

Net Weight

7.42 KG

Shipping Weight

8.41 KG

Shipping Height

470.00 mm

Shipping Width

305.00 mm

Shipping Depth

165.00 mm

Master Carton Units

2.00

Master Carton Dimensions (Length x Width x Height)

18.75 X 12.5 X 13.5 inches

Master Carton Weight

37.05 lbs.

Color

Beige

SCC Codes

1073130420641 2

Units per Pallet

20.00

Environmental

Operating Environment

0 - 40 °C

Operating Relative Humidity

5 - 95%

Operating Elevation

0-3000 meters

Storage Temperature

-15 - 45 °C

Storage Relative Humidity

0 - 95%

Storage Elevation

0-3000 meters

Audible noise at 1 meter from surface of unit

40 dBA

Conformance

Regulatory Approvals

A-tick,C-tick,GOST,NEMKO

Standard Warranty

2 year (manufacturer's defect)

All rights reserved. All APC trademarks are property of American Power Conversion. Other trademarks are property of their respective owners. Specifications are subject to change without notice.