Key Features

- Multi-tasking capabilities for enhanced lesson delivery
- Embrace simplicity and organization with the USB-C one-cable solution, offering 65W of Power Delivery.
- Intuitive user interface and fast app launch for smooth operation.
- Powered by Android 11.



Product **Description**

The ViewBoard IFP33 Series harmonizes a touch display with versatile software to create a comprehensive classroom solution for interactive and engaging learning. This interactive flat panel delivers exceptional image quality in 4K UHD, thanks to cutting-edge bonding technology that provides clearer colors, enhanced contrast, and reduced glare. The 40-point touchscreen interface, equipped with Ultra Fine Touch Technology, empowers students and teachers to collaborate seamlessly, using either their fingers or dual-tip pens, for an intuitive pen-on-paper experience. Powerful built-in front-facing speakers and a USB-C port sort out for a complete and convenient multimedia experience. The ViewBoard IFP33 Series is preinstalled with myViewBoard to offer advanced lesson delivery options for teachers and powerful device management tools for administrators.

Visit Us

www.viewsonic.com



DISPLAY		TOP CAMERA PLATE	
Panel Size:	75"	Yes	
Panel Type:	TFT LCD Module with	EMBEDDED OS	
	DLED Backlight. IPS	Android 11	
Display Area (mm):	1649.664(H) × 927.936(V) (74.6" diagonal)	BUNDLE SOFTWARE	myViewBoard
Aspect Ratio:	16:9	Basic Annotation Software:	Whiteboard
Resolution:	UHD 3840x2160(Pixels)	Pro Annotation Software:	myViewBoard for Windows (Embedded in optional Windows
Colors:	1.07B colors		Slot-in PC)
Brightness:	400 nits (typ.), 450 nits (max.)	Wireless Presentation: Wireless Presentation with Touch	myViewBoard Display Yes
Contrast Ratio:	5000:1 (max. with DCR enabled)	Feedback: Viewboard Cast: SPECIAL FEATURES	Tes
Response Time:	8ms	(combine slot-in	
Viewing Angles:	H=178, V=178	All-in-one USB port:	PC/Android/HDMI USB port) Front "SmartPort™ USB" to all channels.
Backlight Life:	30,000 Hours (Min.)		
Surface Treatment:	Hardness:7H Anti-glare coating	Simple LAN sharing between IFP and slot-in device:	10/100M for Android & Slot-in PC
Orientation:	Landscape	Light Sensor:	Yes
PLATFORM		POWER	
Processor:	Quad-core ARM Cortex (A55*4)	Voltage:	100-240V AC
RAM:	4GB DDR4	Consumption:	150W
	32 GB	ERGONOMICS	
Storage:	32 GB	Wall Mount (VESA®):	800x400
тоисн	Ultra Fine Touch	OPERATING CONDITIONS	
Type/ Tech:	Technology	Temperature (° C):	0°C to 40°C
Touch Point:	40 points touch	Humidity:	20% ~ 80% RH non- condensing
INPUT	HDMI-IN 2.0 x 3	DIMENSIONS (W X H X D)	
HDMI:	(3840x2160 @60Hz)	Physical (inch / mm):	1709 x 1020 x 88 mm / 67.3 x 40.2 x 3.5 in
RGB / VGA:	x1	D. I	1863 x 225 x 1140 mm
Audio:	x1	Packaging (inch / mm):	/ 73.3 x 8.6 x 44.9 in
RS232:	x1	WEIGHT	
OPS:	x1 (Optional Intel Standard OPS)	Net (lb / kg):	104.3lb/47.3kg
WiFi:	x1 (Optional VB-WIFI-	Gross (lb / kg):	133.5lb/60.55kg
	002/VB-WIFI-004/VSB- 050)	REGULATIONS	
OUTPUT	000)	BIS, cTUVus, COC, EPET	
HDMI:	HDMI 2.0 x1	PACKAGE CONTENTS	
		1. 3m power cord by ship area 2. Remote control with AAA battery 3. 3m touch USB cable 4. Touch pen x 2 (VB-PEN-009) 5. Quick Start Guide + Compliance statement 6. RS232 adapter 7. Clamp x 5 8. Camera Plate 9. Screw x 8 (camera 2+2, wall mount 4) 10. HDMI cable 3m	
Audio:	x1		
SPDIF:	x1		
LAN	v2	COMPATIBLE SLOT-IN PC	
RJ45:	x2	VPC2-O series/VPC2-O-1B series/VPC12-WPO-15/16	
Type A:	USB3.0 x4 (Front x2, Rear x2); USB2.0 x1		
Type B:	x2 (Front x1, Rear x1)		
Type C:	Frontx1 (PD65W + DP1.2 + Data USB2.0 + 10M/100M sharing)		
SPEAKERS	room snamg)		
JI LAINLING			

Copyright © ViewSonic Corporation 2000-2023. All rights reserved.

18W x2