LSC701-4K 7,000 ANSI Lumens 4K Laser Installation Projector - ViewSonic Europe



Key Features

- 4K HDR professional-quality visuals
- 7,000 ANSI Lumens offering bright images in any environment
- Up to a 300" ultra-large screen with a lower cost-perinch
- Supports a 21:9 aspect ratio, ideal for Microsoft Teams Rooms
- Installation flexibility: H/V lens shift, 1.6x optical zoom, and H/V keystone correction



Product **Description**

The LSC701-4K is a lamp-free, high-brightness projector designed for commercial, educational, and public spaces. Equipped with 4K resolution and HDR/HLG support, it delivers professional-quality presentations and stunning visuals. Utilizing 2nd generation laser phosphor technology, this projector offers 7,000 ANSI Lumens of brightness for up to 30,000 hours and can project an ultra-large screen up to 300". Ideal for modern workplaces, its 21:9 aspect ratio is optimized for Microsoft Teams Rooms applications, enhancing collaborative environments. Equipped with features like H/V lens shift, 1.6x optical zoom, H/V keystone correction, and 360° projection capabilities, the LSC701-4K offers flexible setup possibilities. Additionally, its comprehensive LAN control ensures seamless integration into existing device management networks.

- 1. Zoom Ring 2. Focus Ring 3. Front IR 4. Rear IR 5. RJ45 6. S/PDIF 7. USB-A (5V/2A)
- 8. HDMI 2.0/HDCP 2.2 9. USB-A (5V/2A) 10. RS232 11. Audio Out 12. HDBaseT 13. AC In 14. LED Indicator

15. Keypad 16. Lens Shift Control Knob x2

Visit Us

www.viewsonic.com



LSC701-4K 7,000 ANSI Lumens 4K Laser Installation Projector - ViewSonic Europe

	WUXGA with 4K	OTHERS	100-240V+/- 10%, 50/60
Native Resolution:	Enhancement	Power Supply Voltage:	(AC in)
Brightness:	7000 (ANSI Lumens)	Power Consumption:	Normal: 390W Standby: <0.5W
Brightness (Center Lumens):	7600	Operating Temperature:	0~40°C
Contrast Ratio:	500:1	Carton:	Brown
Display Color:	1.07 Billion Colors	Net Weight:	7.9kg
Light Source Type:	Laser Phosphor	Gross Weight:	10.93kg
Light Source Life (hours) with Normal Mode:	20000	Dimensions (WxDxH) with Adjustment Foot:	405x358x137mm
Light Source Life (hours) with SuperEco Mode:	30000 (Eco)	Packing Dimensions:	510x498x260mm
Lens:	F=1.5-2.08, f=17.2-27.7mm	OSD Language:	English, German, Frenc Italian, Spanish, Polish, Swedish, Dutch, Portuge Japanese, Simplified Chinese, Traditional Chi Korean, Russian, Turkis Finnish, Norwegian, Dar Indonesian, Hungarian, Czech, Vietnamese, Tha
Projection Offset:	0%+/-5%		
Throw Ratio:	1.2-2.0		
Optical Zoom:	1.6X		
Digital Zoom:	1.0x-2.0x		
Image Size:	30"-300"		total 23 languages
Throw Distance:	0.80-13.35m (100"@2.66m)	User Guide Language:	English, S-Chinese, T- Chinese, Indonesian, Fir French, German, Italian, Japanese, Korean, Polis Portuguese, Russian, Spanish, Swedish, Turki Arabic, Czech, Thai, Vietnamese, total 20 languages
Keystone:	H:+/-25°, V:+/-30°		
Lens Shift V. Range:	+66%,0%		
Lens Shift H. Range:	+29%, -29%		
Audible Noise (Normal):	37dB	STANDARD ACCESSORY	languagoo
Audible Noise (Eco):	26dB	Power Cord:	1
Input Lag:	32ms	Remote Control:	1
Resolution Support:	VGA(640 x 480) to 4K(3840 x 2160)	QSG:	Yes
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p	Air Filter:	Yes
Horizontal Frequency:	15K-135KHz	Warranty Card:	Yes (CN Only)
Vertical Scan Rate:	24-85Hz		Vaa
INPUT	21 00112	Air Filter:	Yes
HDMI:	2 (HDMI 2.0, HDCP 1.4/2.2)	Wall/Ceiling Mount:	PJ-WMK-007
Audio-in (3.5mm):	1		
USB Type A:	2 (5V/2A)		
HDBaseT:	1		
RJ45 Input (Internet):	Yes		
OUTPUT			
Audio-out (3.5mm):	1		
Audio-out (HDMI ARC):	1 (Share with HDMI Input)	-	
S/PDIF:	1		
Speaker:	16W		
USB Type A (Power):	2 (USB2.0 - 5V/2A, share with USB A Input)		
CONTROL			
RS232 (DB 9-pin male):	1		
		-	
RJ45 (LAN control):	1 (share with RJ45 Internet)		

Copyright $\ensuremath{\textcircled{C}}$ ViewSonic Corporation 2000-2024. All rights reserved.