



SPECIFICATIONS

Panel Size	27" (69cm)
Panel Resolution	1920 x 1080 (FHD)
Refresh Rate	165Hz
Response time	1ms
DYNAMIC REFRESH RATE TECHNOLOGY	G-sync Compatible
ACTIVATED RANGE	30 to 165Hz
Panel Type	IPS
Brightness (nits)	300 nits
Viewing Angle	178° (H) / 178° (V)
Aspect Ratio	16:9
Contrast Ratio	1000:1
DCR	100000000:1
Active Display Area (mm)	597.6(H) x 336.15(V)
Pixel Pitch (H x V)	0.31125(H) x 0.31125(V)
Surface Treatment	Anti-glare
Display Colors	1.07B (8bits + FRC)
Video ports	1x Display Port (1.2a) 1x HDMI (2.0b) 1x Type C (DP alt.)
USB ports	2x USB 2.0 Type A 1x USB 2.0 Type B
Audio ports	1x Earphone out
Kensington Lock	Yes
VESA Mounting	100 x 100 mm
Control	5-way OSD navigation joystick
Power Type	External Adaptor 19V 3.42A
Power Input	100~240V, 50~60Hz
Signal Frequency	96.4 to 186.7KHz (H) 30 to 165Hz (V)
Adjustment (Tilt)	-5° ~ 20°
Adjustment (Swivel)	-75° ~ 75°
Adjustment (Pivot)	-90° ~ 90°
Adjustment (Height)	0 ~ 100mm
Dimension (W x H x D)	614.9 x 532.7 x 206.7 mm / 24.21 x 20.97 x 8.14 inch
Carton Dimension (W X H X D)	730 x 490 x 220 mm / 28.74 x 19.29 x 8.66 inch
Weight (NW / GW)	6.05kg / 8.7kg 13.34lbs / 19.18lbs

FEATURES



Frameless Design	Yes
Note	Display Port: 1920 x 1080 (Up to 165Hz) HDMI: 1920 x 1080 (Up to 165Hz) The color gamut follows the CIE 1976 testing standard.

CONNECTIONS



1. 5-way joystick navigator
2. 1x Display Port (1.2a)
3. 2x HDMI (2.0b)
4. 1x Type C (DP alt.)
5. 1x Earphone out
6. 1x USB 2.0 Type B
7. 2x USB 2.0 Type A
8. 1x DC jack
9. 1x Kensington lock
- 10.