

ViewSonic  PROJECTOR
PS502W


Key Features

- 4,000 ANSI Lumens offering clear images in any environment
- 0.52 Short throw ratio for minimal space consumption
- Up to 300" ultra large screen with lower cost-per-inch
- Easy and flexible connection: dual HDMI ports, USB Type-A port
- Convenient software updates for projectors via USB connection



Product Description

The PS502W is ViewSonic's high brightness WXGA short throw business/education projector. Boasting 4,000 ANSI Lumens of high brightness, the projector offers clear images of up-to-300" large screen in meeting rooms, classrooms, or any other bright environment. With 0.52 short throw ratio, the projector can provide 100" large screen size from only 1.1 m away without being obstructed by shadows, allowing for a large screen even in small spaces. The dual HDMI ports allow you to flexibly connect to multiple devices, easily switching between content sources. The USB Type-A port can supply power to HDMI wireless dongles, making wireless content streaming more convenient. The projector also allows software updates via USB cable connection with simply your laptops, skipping trips to service centers.



Visit Us www.viewsonic.com



SPECIFICATION

Native Resolution:	1280x800
Brightness:	4000 (ANSI Lumens)
Contrast Ratio with SuperEco Mode:	15000:1
Display Color:	1.07 Billion Colors
Light Source Type:	240W UHP Lamp
Light Source Life (hours) with Normal Mode:	4000
Light Source Life (hours) with SuperEco Mode:	12000
Lens:	F=2.8, f=7.51mm
Projection Offset:	112.4%+/-4%
Throw Ratio:	0.52
Optical Zoom:	Fixed
Digital Zoom:	0.8x-2.0x
Image Size:	60"-300"
Throw Distance:	0.67m-3.36m (87"@0.97m)
Keystone:	+19°/-19° (V)
Audible Noise (Normal):	34dB
Audible Noise (Eco):	25dB
Input Lag:	33.2ms
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K-102KHz
Vertical Scan Rate:	23-120Hz

INPUT

Computer in (share with component):	1
HDMI:	2 (HDMI 1.4/ HDCP 1.4)
Audio-in (3.5mm):	1

OUTPUT

Monitor out:	1
Audio-out (3.5mm):	1
Speaker:	16W
USB Type A (Power):	1 (5V/1.5A)

CONTROL

RS232 (DB 9-pin male):	1
USB Type A (Services):	1 (share with USB A Output)

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz (AC in)
Power Consumption:	Normal: 295W Standby: <0.5W
Operating Temperature:	0~40°C
Carton:	Brown
Net Weight:	2.87kg
Gross Weight:	4.08Kg
Dimensions (WxDxH) with Adjustment Foot:	309x234x115mm
Packing Dimensions:	400x337x168mm
OSD Language:	English, German, French, Swedish, Spanish, Portuguese, Polish, Dutch, T. Chinese, S.Chinese, Finnish, Korean, Russian, Hungarian, Czech, Arabic, Thai, Turkish, Vietnamese, Indonesian, Greek, Italian, Total 22 languages
User Guide Language:	English, S-Chinese, T-Chinese, Finnish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Total 15 languages

STANDARD ACCESSORY

Power Cord:	1
VGA Cable:	1
Remote Control:	1
QSG:	Yes
Lens Cover:	Yes
Air Filter:	Yes (CN Only)
Warranty Card:	Yes (CN Only)

OPTIONAL ACCESSORY

Lamp/Light Source:	RLC-128
Air Filter:	RSPL
Wall/Ceiling Mount:	PJ-WMK-305 PJ-WMK-007
Carry Bag:	PJ-CASE-008

