



APC Back-UPS 950VA, 230V, AVR, French Sockets

BX950MI-FR

Call for More Information

- Includes: User manual

| Output | |
|----------------------------------|-------------------------------------|
| Output power capacity | 520 Watts / 950VA |
| Max Configurable Power (Watts) | 520 Watts / 950VA |
| Nominal Output Voltage | 230V |
| Output Frequency (sync to mains) | 50/60 Hz +/- 1 Hz Sync to mains |
| Topology | Standby |
| Waveform type | Stepped approximation to a sinewave |
| Transfer Time | 6 ms typical : 10 ms maximum |

| Input | |
|---|--------------------------------|
| Nominal Input Voltage | 230V |
| Input frequency | 50/60 Hz +/- 5 Hz Auto-sensing |
| Cord Length | 1.2meters |
| Input voltage range for main operations | 140 - 300V |
| Number of Power Cords | 1 |
| Input Power Factor at Full Load | 0.54 |

| Batteries & Runtime | |
|-------------------------------|--|
| Battery type | Lead-acid battery |
| Typical recharge time | 8hour(s) |
| Expected Battery Life (years) | 1 - 2 |
| Efficiency | View Efficiency Graph (Available in Technical Tab on site) |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

| Communications & Management | |
|-----------------------------|---|
| Interface Port(s) | USB |
| Control panel | LED Status display with on line : on battery |
| Audible Alarm | Alarm when on battery : distinctive low battery alarm |

| Surge Protection and Filtering | |
|--------------------------------|---|
| Surge energy rating | 273Joules |
| Data Line Protection | RJ45 10/100/1000 Base-T Ethernet protection |

| Physical | |
|-----------------|----------------|
| Maximum Height | 160MM, 16.0CM |
| Maximum Width | 120MM, 12.0CM |
| Maximum Depth | 355MM, 35.5CM |
| Net Weight | 6.1KG |
| Shipping weight | 6.6KG |
| Shipping Height | 250MM, 25.0CM |
| Shipping Width | 197MM, 19.7CM |
| Shipping Depth | 430MM, 43.0CM |
| Color | Black |
| SCC Codes | 10731304413568 |

| Environmental | |
|---|---------------------------|
| Operating Temperature | 0 - 40 °C |
| Operating Relative Humidity | 0 - 95 (Non-condensing) % |
| Operating Elevation | 0 - 914.4meters |
| Storage Temperature | -15 - 40 °C |
| Storage Elevation | 0 - 914.4meters |
| Audible noise at 1 meter from surface of unit | 40.0dBA |
| Protection Class | IP20 |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Back-UPS 950VA, 230V, AVR, French Sockets | BX950MI-FR | Downloaded on 10/02/2020 (EST)

| Conformance | |
|-----------------------------|---|
| Approvals | CB , CE, EN/IEC 62040-1, EN/IEC 62040-2 |
| Equipment protection policy | Lifetime : 50000 euros |
| Standard warranty | 2 years repair or replace |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.