

**ViewSonic**  LCD DISPLAY  
**VG2208A-HD**

### Key Features

- SuperClear® IPS panel with Full HD 1080p resolution
- 100Hz variable refresh rate delivers fluid visuals
- Flexible connectivity via HDMI, DisplayPort, and VGA
- Ergonomic tilt, swivel, pivot, and height adjustment capabilities
- TCO, EnergyStar, EPEAT Silver certified for sustainability



### Product Description

The ViewSonic VG2208A-HD is a 22" Full HD monitor featuring HDMI, DisplayPort, and VGA inputs for business and home use. The optimal screen performance and comfortable viewing without tearing or stuttering is delivered through 100hz variable refresh rate, eye-care technology, and various ViewMode presets. Simply expand your workspace and experience truly seamless, ergonomic multitasking on just one screen with a VESA-compatible mount at a low power consumption.



1. Menu Control Panel
2. DisplayPort
3. HDMI
4. VGA
5. Audio Out
6. Power In

7. VESA Compatible(Wall Mount 100x100mm)

**Visit Us** [www.viewsonic.com](http://www.viewsonic.com)

**DISPLAY**

Display Size (in.):	22
Viewable Area (in.):	21.5
Panel Type:	IPS Technology
Resolution:	1920 x 1080
Resolution Type:	FHD (Full HD)
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	50M:1
Light Source:	LED
Brightness:	250 cd/m <sup>2</sup> (typ)
Colors:	16.7M
Color Space Support:	8 bit (6 bit + FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	5ms
Response Time (GTG w/OD):	5ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	100
Variable Refresh Rate Technology:	Yes
Low Blue Light:	Software solution
Flicker-Free:	Yes
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)
Pixel Size:	0.249 mm (H) x 0.241 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

**COMPATIBILITY**

PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	1920x1080

**CONNECTOR**

VGA:	1
3.5mm Audio Out:	1
HDMI 1.4:	1
DisplayPort:	1
Power in:	3-pin Socket (IEC C14 / CEE22)

**POWER**

Eco Mode (Conserve):	10W
Eco Mode (optimized):	11W
Consumption (typical):	13W
Consumption (max):	17W
Voltage:	AC 100-240V
Stand-by:	0.3W
Power Supply:	Internal Power Supply

**ADDITIONAL HARDWARE**

Kensington Lock Slot:	1
-----------------------	---

**CONTROLS**

Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display:	Input Select, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

**OPERATING CONDITIONS**

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

**WALL MOUNT**

VESA Compatible:	100 x 100 mm
------------------	--------------

**INPUT SIGNAL**

Frequency Horizontal:	RGB Analog: 24 ~ 86KHz, HDMI (v1.4): 24 ~ 115KHz, DisplayPort (v1.2): 24 ~ 115KHz
Frequency Vertical:	RGB Analog: 48 ~ 75Hz, HDMI (v1.4): 48 ~ 100Hz, DisplayPort (v1.2): 48 ~ 100Hz

**VIDEO INPUT**

Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2)
Analog Sync:	Separate - RGB Analog

**ERGONOMICS**

Height Adjust (mm):	100
Swivel:	340°
Tilt (Forward/Back):	-3.5° / 23°
Pivot (Right/Left):	90° / 0°

**WEIGHT (IMPERIAL)**

Net (lbs):	8.4
Net Without Stand (lbs):	4.9
Gross (lbs):	11.2

**WEIGHT (METRIC)**

Net (kg):	3.8
Net Without Stand (kg):	2.2
Gross (kg):	5.1

**DIMENSIONS (IMPERIAL) (WXHXD)**

Packaging (in.):	21.7 x 13.7 x 6
Physical (in.):	19.4 x 14.11~18.04 x 8.04
Physical Without Stand (in.):	19.4 x 11.28 x 1.69

**DIMENSIONS (METRIC) (WXHXD)**

Packaging (mm):	550 x 348 x 153
Physical (mm):	492.86 x 358.32~458.32 x 204.31
Physical Without Stand (mm):	492.86 x 286.48 x 43.01

**GENERAL**

Regulations:	Energy Star, EPEAT, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 9.0, EAC, UkrSEPRO
PACKAGE CONTENTS:	VG2208A-HD x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market
Power Management:	Energy Star standards, EPEAT