

## Key Features

- SuperClear® IPS panel with Full HD 1080p resolution
- 100Hz variable refresh rate delivers fluid visuals
- USB hub with 1 upstream, 2 downstream ports, and HDMI, Display Port inputs for easy connectivity
- Ergonomic tilt, swivel, pivot, and height adjustment capabilities
- TCO, EnergyStar, EPEAT Silver certified for sustainability



## Product Description

The ViewSonic VG2208A is a 22" Full HD monitor featuring HDMI, DisplayPort, USB-B upstream and USB-A downstream inputs for business and home use. The optimal screen performance and comfortable viewing without tearing or stuttering is delivered through 100hz variable refresh rate, eye-care technology, and various ViewMode presets. Simply expand your workspace and experience truly seamless, ergonomic multitasking on just one screen with a VESA-compatible mount at a low power consumption.





www.viewsonic.com

## 12/3/24, 4:52 PM

## VG2208A 22" Full HD 100Hz Ergonomic Monitor with USB Hub - ViewSonic Europe

DISPLAY		WEIGHT (IMPERIAL)	
Display Size (in.):	22	Net (lbs):	8.4
Viewable Area (in.):	21.5	Net Without Stand (Ibs):	4.9
Panel Type:	IPS Technology	Gross (Ibs):	11.2
Resolution:	1920 x 1080	WEIGHT (METRIC)	
Resolution Type:	FHD (Full HD)	Net (kg):	3.8
Static Contrast Ratio:	1,000:1 (typ)	Net Without Stand (kg):	2.2
Dynamic Contrast Ratio:	50M:1	Gross (kg):	5.1
Light Source:	LED	DIMENSIONS (IMPERIAL) (W	VXHXD)
Brightness:	250 cd/m² (typ)	Packaging (in.):	21.7 x 13.7 x 6
Colors:	16.7M	Physical (in.):	19.4 x 14.11~18.04 x 8.04
Color Space Support:	8 bit (6 bit + FRC)	Physical Without Stand (in.):	19.4 x 11.28 x 1.69
		DIMENSIONS (METRIC) (WX	
Aspect Ratio:	16:9 -	Packaging (mm):	550 x 348 x 153
Response Time (Typical GTG):	5ms	Physical (mm):	492.86 x 358.32~458.32 x 204.31
Response Time (GTG w/OD):	5ms	Physical Without Stand (mm):	492.86 x 286.48 x 43.01
Viewing Angles:	178º horizontal, 178º vertical	GENERAL	402.00 x 200.40 x 40.01
Backlight Life (Hours):	30000 Hrs (Min)	GENERAL	Energy Star, EPEAT, CE, CE EMC, CB, RoHS, ErP,
Curvature:	Flat	Regulations:	REACH, WEEE, TCO 9.0, EAC, UkrSEPRO
Refresh Rate (Hz):	100		VG2208A x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI
Variable Refresh Rate Technology:	Yes	PACKAGE CONTENTS:	Cable (v1.4; Male-Male) x1, USB A/B Cable (v3.2; Ma Male) x1, Quick Start Guide x1
Low Blue Light:	Software solution	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Flicker-Free:	Yes	Warranty:	*Warranty offered may differ from market to market
Color Gamut:	NTSC: 72% size (Typ)	Power Management:	Energy Star standards, EPEAT
	sRGB: 104% size (Typ)		
Pixel Size:	0.249 mm (H) x 0.241 mm (V)		
Surface Treatment:	Anti-Glare, Hard Coating (3H)		
COMPATIBILITY			
PC Resolution (max):	1920x1080		
Mac® Resolution (max):	1920x1080		
PC Operating System:	Windows 10/11 certified; macOS tested		
Mac® Resolution (min):	1920x1080		
CONNECTOR			
USB 3.2 Type A Down Stream:	2		
USB 3.2 Type B Up Stream:	1		
3.5mm Audio Out:	1		
HDMI 1.4:	1		
DisplayPort:	1		
Power in:	3-pin Socket (IEC C14 / CEE22)		
AUDIO			
	2Watts x2		
Internal Speakers: POWER	ZWalls XZ		
	1014		
Eco Mode (Conserve):	10W		
Eco Mode (optimized):	12W		
Consumption (typical):	14W		
Consumption (max):	23W		
Voltage:	AC 100-240V		
Stand-by:	0.3W		
Power Supply:	Internal Power Supply		
ADDITIONAL HARDWARE			
B B I I I I I I I I I I I I I I I I I I			
Kensington Lock Slot:	1		
	1		
Kensington Lock Slot:	1 Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)		
Kensington Lock Slot: CONTROLS Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) Input Select, Audio Adjust, ViewMode, Color Adjust,		
Kensington Lock Slot: CONTROLS Physical Controls: On Screen Display:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)		
Kensington Lock Slot: CONTROLS Physical Controls: On Screen Display: CPERATING CONDITIONS	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
Kensington Lock Slot: CONTROLS Physical Controls: On Screen Display: DPERATING CONDITIONS Temperature:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu 32°F to 104°F (0°C to 40°C)		
Kensington Lock Slot: CONTROLS Physical Controls: On Screen Display: CPERATING CONDITIONS	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
Kensington Lock Slot: CONTROLS Physical Controls: On Screen Display: DPERATING CONDITIONS Temperature: Humidity (non-condensing):	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu 32°F to 104°F (0°C to 40°C)		
Kensington Lock Slot: CONTROLS Physical Controls: On Screen Display: DPERATING CONDITIONS Temperature: Humidity (non-condensing): WALL MOUNT	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu 32°F to 104°F (0°C to 40°C) 20% to 90%		
Kensington Lock Slot: CONTROLS Physical Controls: On Screen Display: DPERATING CONDITIONS Temperature: Humidity (non-condensing): NALL MOUNT VESA Compatible:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu 32°F to 104°F (0°C to 40°C) 20% to 90%		
Kensington Lock Slot: CONTROLS Physical Controls: On Screen Display: DPERATING CONDITIONS Temperature: Humidity (non-condensing): WALL MOUNT VESA Compatible: NPUT SIGNAL Frequency Horizontal:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu 32°F to 104°F (0°C to 40°C) 20% to 90% 100 x 100 mm		
Kensington Lock Slot: CONTROLS Physical Controls: On Screen Display: DPERATING CONDITIONS Temperature: Humidity (non-condensing): WALL MOUNT VESA Compatible: NPUT SIGNAL Frequency Horizontal: Frequency Vertical:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)   Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu   32°F to 104°F (0°C to 40°C)   20% to 90%   100 x 100 mm   24 ~ 115KHz		
Kensington Lock Slot: CONTROLS Physical Controls: On Screen Display: DERATING CONDITIONS Temperature: Humidity (non-condensing): WALL MOUNT VESA Compatible: NPUT SIGNAL Frequency Horizontal: Frequency Vertical: //IDEO INPUT	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu 32°F to 104°F (0°C to 40°C) 20% to 90% 100 x 100 mm 24 ~ 115KHz 48 ~ 100Hz		
Kensington Lock Slot: CONTROLS Physical Controls: On Screen Display: DERATING CONDITIONS Temperature: Humidity (non-condensing): NALL MOUNT VESA Compatible: NPUT SIGNAL Frequency Horizontal: Frequency Vertical: //DEO INPUT Digital Sync:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)   Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu   32°F to 104°F (0°C to 40°C)   20% to 90%   100 x 100 mm   24 ~ 115KHz		
Kensington Lock Slot: CONTROLS Physical Controls: On Screen Display: DERATING CONDITIONS Temperature: Humidity (non-condensing): NALL MOUNT VESA Compatible: NPUT SIGNAL Frequency Horizontal: Frequency Vertical: //DEO INPUT Digital Sync: ERGONOMICS	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)   Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu   32°F to 104°F (0°C to 40°C)   20% to 90%   100 x 100 mm   24 ~ 115KHz 48 ~ 100Hz   TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2)		
Kensington Lock Slot: CONTROLS Physical Controls: On Screen Display: DERATING CONDITIONS Temperature: Humidity (non-condensing): VALL MOUNT VESA Compatible: NPUT SIGNAL Frequency Horizontal: Frequency Horizontal: Frequency Vertical: //IDEO INPUT Digital Sync: ERGONOMICS Height Adjust (mm):	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)   Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu   32°F to 104°F (0°C to 40°C)   20% to 90%   100 x 100 mm   24 ~ 115KHz   48 ~ 100Hz   TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2)   100		
Kensington Lock Slot: CONTROLS Physical Controls: On Screen Display: DERATING CONDITIONS Temperature: Humidity (non-condensing): NALL MOUNT VESA Compatible: NPUT SIGNAL Frequency Horizontal: Frequency Vertical: //DEO INPUT Digital Sync: ERGONOMICS	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)   Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu   32°F to 104°F (0°C to 40°C)   20% to 90%   100 x 100 mm   24 ~ 115KHz 48 ~ 100Hz   TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2)		

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.