ViewSonic ME VG2409-MHDU-2

Key Features

- Integrated USB-C workstation offers audiovisual and data transfer, and power delivery up to 65W
- USB 3.2 hub with 1 upstream, 2 downstream ports, HDMI, and DisplayPort inputs for easy connectivity
- SuperClear® IPS panel with 100Hz variable refresh rate delivers fluid visuals
- Ergonomic tilt, swivel, pivot and height adjustment capabilities
- TCO, EnergyStar, EPEAT Silver certified for sustainability



Product Description

The ViewSonic VG2409-MHDU-2 is a 24" FHD monitor featuring USB 3.2 Hub with 1 upstream, 2 downstream ports, HDMI, and DisplayPort for business and home use. Simplify your work with just one cable that provides audiovisual, data and 65W power transfer. The 100hz variable refresh rate, Eye ProTech technology, and various ViewMode presets cater for optimal screen performance and comfortable viewing without tearing or stuttering. Expand your workspace and experience truly seamless, ergonomic multitasking on just one screen with a VESA-compatible mount at low energy consumption.



Visit Us www.viewsonic.com



9/25/24, 9:55 AM

VG2409-MHDU-2 24" Full HD Ergonomic IPS Monitor with USB-C Hub - ViewSonic Europe

:55 AM	VG2409-MHDU-2 24" Full HD Erg	onomic IPS Monitor with	USB-C Hub - ViewSonic Europe
DISPLAY		ERGONOMICS	
Display Size (in.):	24	Height Adjust (mm):	130
Viewable Area (in.):	23.8	Swivel:	360°
Panel Type:	IPS Technology	Tilt (Forward/Back):	-3.5° / 28°
Resolution:	1920 x 1080	Pivot (Right/Left):	90° / 90°
Resolution Type:	FHD (Full HD)	WEIGHT (IMPERIAL)	
Static Contrast Ratio:	1,300:1 (typ)	Net (lbs):	12.3
Dynamic Contrast Ratio:	50M:1	Net Without Stand (lbs):	7.7
Light Source:	LED	Gross (lbs):	15.9
Brightness:	350 cd/m² (typ)	WEIGHT (METRIC)	
Colors:	16.7M	Net (kg):	5.6
Color Space Support:	8 bit (6 bit + FRC)	Net Without Stand (kg):	3.5
Aspect Ratio:	16:9	Gross (kg):	7.2
Response Time (Typical GTG):	4ms	DIMENSIONS (IMPERIAL) (W	VXHXD)
Response Time (GTG w/OD):	4ms	Packaging (in.):	24.5 x 20.5 x 5.7
Viewing Angles:	178º horizontal, 178º vertical	Physical (in.):	21.25 x 15.35~20.47 x 9.18
		Physical Without Stand (in.):	21.25 x 12.72 x 2
Backlight Life (Hours):	30000 Hrs (Min)	DIMENSIONS (METRIC) (WX	
Curvature:	Flat	Packaging (mm):	622 x 520 x 144
Refresh Rate (Hz):	100	Physical (mm):	539.7 x 389.89~519.89 x 233.29
Variable Refresh Rate Technology:	Yes	Physical Without Stand (mm):	539.7 x 323.18 x 50.9
Low Blue Light:	Software solution	GENERAL	
Flicker-Free:	Yes		Energy Star, EPEAT, CE, CE EMC, CB, RoHS, ErP,
	NTSC: 72% size (Typ)	Regulations:	REACH, WEEE, TCO 9.0, EAC, UkrSEPRO
Color Gamut:	sRGB: 104% size (Typ)		VG2409-MHDU-2 x1, 3-pin Plug (IEC C13 / CEE22) x1
Pixel Size:	0.275 mm (H) x 0.275 mm (V)	PACKAGE CONTENTS:	HDMI Cable (v1.4; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1,
Surface Treatment:	Anti-Glare, Hard Coating (3H)		Quick Start Guide x1
COMPATIBILITY		Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
PC Resolution (max):	1920x1080	Warranty:	*Warranty offered may differ from market to market
Mac® Resolution (max):	1920x1080	Power Management:	Energy Star standards, EPEAT
PC Operating System:	Windows 10/11 certified; macOS tested	· · · · · · · · · · · · · · · · · · ·	
Mac® Resolution (min):	1920x1080		
CONNECTOR			
USB 3.2 Type A Down Stream:	2		
USB 3.2 Type B Up Stream:	1		
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1 (65W power charger)		
3.5mm Audio Out:	1		
HDMI 1.4:	1		
DisplayPort:	1		
Power in:	3-pin Socket (IEC C14 / CEE22)		
AUDIO			
Internal Speakers:	2.5Watts x2		
POWER			
Eco Mode (Conserve):	18W		
Eco Mode (optimized):	20W		
Consumption (typical):	22W		
Consumption (typical):	22W 24W		
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	Internal Power Supply		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
Cable Organization:	Yes		
CONTROLS			
Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS	3 3 3 5 5 5 5 5 5 5 5 5 5		
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing): WALL MOUNT	20% to 90%		
VESA Compatible:	100 x 100 mm		
	100 x 100 mm		
	20 - 125// 47		
Frequency Horizontal:	30 ~ 125KHz		
Frequency Vertical:	48 ~ 100Hz		
VIDEO INPUT			
Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2), Micro- Packet - Type C		

