

## Key Features

- Integrated USB TypeC and Ethernet
- 4K UHD with two HDMI ports
- Ergonomic design
- vDisplay Manager software for multitasking
- Lower total cost of ownership



## Product **Description**

The ViewSonic VG56 docking monitor series will keep the workstation tidy and productive with USB Type-C and Ethernet connectivity that turn your monitor into a hub for charging, data, network, and devices, while reducing clutter on your desk and simplifying cable management. With a 27" 4K UHD display that delivers larger and stunning visuals, the VG2756-4K monitor expands your productivity, especially if you work in graphic design or software engineering. A range of ergonomic features such as 40-degree tilt, swivel, bi-directional pivot and height adjustment, along with eye-care technology let you stay comfortable at work all day. In addition, the supported vDisplay Manager software for multi-tasking provides efficient on-screen display control. The monitor and quick release stand ship in an eco-friendly, biodegradable package, thus minimizing total cost of ownership.





## ViewSonic VG2756-4K 27" 4K UHD Docking Monitor

1	VIEWSOIIIC	/G2756-4K 27" 4K UHD Do	
DISPLAY		INPUT SIGNAL	
Display Size (in.):	27	Frequency Horizontal:	15 ~ 150KHz
Viewable Area (in.):	27	Frequency Vertical:	24 ~ 75Hz
Panel Type:	IPS Technology	VIDEO INPUT	
Resolution:	3840 x 2160	Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.2), Micro-Packet -
Resolution Type:	UHD (Ultra HD)		Туре С
Static Contrast Ratio:	1,000:1 (typ)	ERGONOMICS	
Dynamic Contrast Ratio:	80M:1	Height Adjust (mm):	130
Light Source:	LED	Swivel:	120°
Brightness:	350 cd/m² (typ)	Tilt (Forward/Back):	-5° / 40°
Colours:	1.07B	Pivot (Right/Left):	90° / 90°
Colour Space Support:	10 bit (8 bit + A-FRC)	WEIGHT (IMPERIAL)	
Aspect Ratio:	16:9	Net (lbs):	16.5
Response Time (Typical GTG):	5ms	Net Without Stand (lbs):	11.2
Response Time (GTG w/OD):	5.8ms	Gross (lbs):	23.6
Viewing Angles:	178º horizontal, 178º vertical	WEIGHT (METRIC)	
Backlight Life (Hours):	30000 Hrs (Min)	Net (kg):	7.5
Curvature:	Flat	Net Without Stand (kg):	5.1
Refresh Rate (Hz):	60	Gross (kg):	10.7
Blue Light Filter:	Yes	DIMENSIONS (IMPERIAL) (W	
Flicker-Free:	Yes	Packaging (in.):	27.2 x 16.9 x 8.6
Color Gamut:	NTSC: 77% size (Typ)	Physical (in.):	24.1 x 15.99~20.99 x 8
	sRGB: 109% size / 100% coverage (Typ)	Physical Without Stand (in.):	24.1 x 14.2 x 2
Pixel Size:	0.155 mm (H) x 0.155 mm (V)	DIMENSIONS (METRIC) (WX	
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Packaging (mm):	692 x 430 x 218
COMPATIBILITY		Physical (mm):	612 x 406.19~533.24 x 202
PC Resolution (max):	3840x2160	Physical Without Stand (mm):	612 x 362 x 52
Mac® Resolution (max):	3840x2160	GENERAL	
PC Operating System:	Windows 11 certified; macOS tested	Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, MX-CoC, Mexic Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 9.0, EAC
Mac® Resolution (min):	3840x2160		
	0010/2100		UkrSEPRO, UKCA
USB 3.2 Type A Down Stream:	2		VG2756-4K x1, 3-pin Plug (IEC C1
USB 3.2 Type B Up Stream:	1	PACKAGE CONTENTS:	CEE22) x1, HDMI Cable (v2.0; Ma Male) x1, USB Type-C Cable (Male
USB 3.2 Type C Up Stream;			Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x
DisplayPort Alt mode :	1 (90W power charger)	Recycle/Disposal:	Please dispose of in accordance w
HDMI 2.0 (with HDCP 2.2):	2	·····, ····	local, state or federal laws.
DisplayPort:	1	Warranty:	*Warranty offered may differ from market to market
Power in:	3-pin Socket (IEC C14 / CEE22)	Power Management:	Energy Star standards, EPEAT
Ethernet LAN (RJ45):	1		
AUDIO			
Internal Speakers:	2Watts x2		
POWER			
Eco Mode (Conserve):	16.81W		
Eco Mode (optimized):	21.12W		
Consumption (typical):	26.35W		
Consumption (max):	38.94W		
Voltage:	AC 100-240V		
Stand-by:	0.5W	-	
Power Supply:	Internal Power Supply		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
Cable Organization:	Yes		
CONTROLS			
Physical Controls:	Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
· Humidity (non-condensing): WALL MOUNT	20% to 90%		
VESA Compatible:	100 x 100 mm		
Lon oompanble.			

Copyright © ViewSonic Corporation 2000-2022. All rights reserved.