

ViewSonic® LCD DISPLAY VG2756V-2K

Key Features

- Adjustable angles' webcam with built-in LED fill lights
- Peace of mind with pop-up webcam to enhance privacy
- Clear audio delivery with AI-powered two-way noise-reduction on both speakers and mic-phone
- Directly open a QR code via built-in webcam by vDisplay Manager
- Easy connection and charging with USB-C docking



Product Description

The ViewSonic VG2756V-2K is a 27" QHD video conferencing monitor designed to deliver out-of-the-box video conferencing and high-quality live streaming. The built-in 5MP webcam with LED fill light allows you to better frame yourself during video calls through varied camera angles, while the pop-up design ensures total privacy and security when not in use. Providing the full spectrum of ergonomic flexibility, the VG2756V-2K can tilt, swivel, pivot, and height adjust to adapt to any setup or workflow. The AI noise-cancelling microphone and dual front-facing speakers ensure you can hear and be heard with absolute clarity and professionalism. Combined with the vDisplay Manager productivity software for efficient multi-tasking and streamlined on-screen display control, the VG2756V-2K is the complete solution for anybody looking for a world-class live streaming or video communication experience.

Visit Us www.viewsonic.com

DISPLAY

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS Technology
Resolution:	2560 x 1440
Resolution Type:	QHD (Quad HD)
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	80M:1
Light Source:	LED
Brightness:	350 cd/m ² (typ)
Colors:	16.7M
Color Space Support:	8 bit true
Aspect Ratio:	16:9
Response Time (Typical GTG):	5ms
Response Time (GTG w/OD):	5ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	60
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	NTSC: 76% size (Typ) sRGB: 108% size / 100% coverage (Typ)
Pixel Size:	0.233 mm (H) x 0.233 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	2560x1440
Mac® Resolution (max):	2560x1440
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	2560x1440

CONNECTOR

USB 3.2 Type A Down Stream:	2
USB 3.2 Type B Up Stream:	1
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1 (90W power charger)
3.5mm Audio Out:	1
HDMI 1.4:	1
DisplayPort:	1
Power in:	3-pin Socket (IEC C14 / CEE22)
Ethernet LAN (RJ45):	1

AUDIO

Internal Speakers:	5Watts x2
--------------------	-----------

POWER

Eco Mode (Conserve):	23.6W
Eco Mode (optimized):	26.8W
Consumption (typical):	30.6W
Consumption (max):	35.9W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	Internal Power Supply

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
Webcam:	5.0M pixel
Cable Organization:	Yes
Microphone:	Yes

CONTROLS

Physical Controls:	Key 1 (audio focus), Key 2, Key 3, Key 4, Key 5, Key 6 (power)
On Screen Display:	Input Select, Conference Mode, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	15 ~ 90KHz
Frequency Vertical:	49 ~ 75Hz

VIDEO INPUT

Digital Sync:	TMD5 - HDMI (v1.4), PCI-E - DisplayPort (v1.2), Micro-Packet - Type C
---------------	---

ERGONOMICS

Height Adjust (mm):	110
Swivel:	120°
Tilt (Forward/Back):	-5° / 40°
Pivot (Right/Left):	90° / 90°

WEIGHT (IMPERIAL)

Net (lbs):	18.4
Net Without Stand (lbs):	12.7
Gross (lbs):	25.3

WEIGHT (METRIC)

Net (kg):	8.4
Net Without Stand (kg):	5.8
Gross (kg):	11.5

DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.):	27.1 x 17.8 x 8.9
Physical (in.):	24.1 x 16.67~21 x 8.6
Physical Without Stand (in.):	24.1 x 15.4 x 2.2

DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	689 x 452 x 225
Physical (mm):	613 x 423.38~533.38 x 217
Physical Without Stand (mm):	613 x 390 x 57

GENERAL

Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 9.0, EAC, UkrSEPRO, UKCA, BSMI, RCM
PACKAGE CONTENTS:	VG2756V-2K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market
Power Management:	Energy Star standards, EPEAT