

ViewSonic® LCD DISPLAY VG2757V-2K

Key Features

- Instant, secure access to your digital workspace using **Windows Hello**
- Crystal-clear video with a built-in **Zoom® Certified 5MP pop-up camera with LED fill lights, microphone, and 5W speakers**
- **Integrated docking station** with Ethernet, Daisy Chain capability, and dual USB-C ports for seamless connectivity
- 15W quick charging for mobile devices via **USB-C connection**
- Flicker-free, low blue light screen with **Eye ProTech+** for always-on eye protection



Product Description

The VG2757V-2K is a 27" QHD videoconferencing monitor featuring Windows Hello compatibility. It boasts a Zoom® Certified QHD pop-up webcam that delivers exceptional audiovisuals and discreetly hides away for privacy when not in use. With Windows Hello, it ensures secure facial recognition for swift and convenient logins, eliminating the dependency on passwords. Equipped with 90W and 15W USB-C ports, ethernet, and daisy-chain support, the VG2757V-2K serves as a complete integrated docking station for charging, data transfer, and network connectivity, effectively reducing cable clutter. Its extensive ergonomic flexibility allows tilt, swivel, pivot, and height adjustments for various workflows. Enhanced by vDisplay Manager software for efficient multitasking and on-screen display controls, it offers a comprehensive videoconferencing solution.

Visit Us www.viewsonic.com



DISPLAY

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS Technology
Resolution:	2560 x 1440
Resolution Type:	QHD (Quad HD)
Static Contrast Ratio:	1,300:1 (typ)
Dynamic Contrast Ratio:	1.4/2.2
High Dynamic Range:	80M:1
Light Source:	LED
Brightness:	350 cd/m ² (typ)
Colors:	16.7M
Color Space Support:	8 bit true
Aspect Ratio:	16:9
Response Time (Typical GTG):	5ms
Response Time (GTG w/OD):	5ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	100
Low Blue Light:	Hardware solution
Flicker-Free:	Yes
Color Gamut:	NTSC: 76% size (Typ) sRGB: 108% size / 100% coverage (Typ)
Pixel Size:	0.233 mm (H) x 0.233 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	2560x1440
Mac® Resolution (max):	2560x1440
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	2560x1440

CONNECTOR

USB 3.1 Type C - Downstream:	1
USB 3.2 Type A Down Stream:	3
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1 (90W power charger)
3.5mm Audio Out:	1
HDMI 2.0:	1
DisplayPort:	1
DisplayPort Out:	1
Power in:	3-pin Socket (IEC C14 / CEE22)
Ethernet LAN (RJ45):	1

AUDIO

Internal Speakers:	5Watts x2
--------------------	-----------

POWER

Eco Mode (Conserve):	24.36W
Eco Mode (optimized):	26.75W
Consumption (typical):	29.77W
Consumption (max):	34.29W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	Internal Power Supply

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
Webcam:	5.0M pixel
Cable Organization:	Yes
Microphone:	Yes

CONTROLS

Physical Controls:	Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power)
On Screen Display:	Input Select, Conference Mode, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	15 ~ 150KHz
Frequency Vertical:	50 ~ 100Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4), Micro-Packet - Type C
---------------	---

ERGONOMICS

Height Adjust (mm):	110
Swivel:	120°
Tilt (Forward/Back):	-5° / 40°
Pivot (Right/Left):	90° / 90°

WEIGHT (IMPERIAL)

Net (lbs):	17.7
Net Without Stand (lbs):	12
Gross (lbs):	25.3

WEIGHT (METRIC)

Net (kg):	8
Net Without Stand (kg):	5.5
Gross (kg):	11.5

DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.):	27.1 x 17.8 x 8.9
Physical (in.):	24.12 x 16.67~21 x 8.55
Physical Without Stand (in.):	24.12 x 15.36 x 2.24

DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	689 x 452 x 225
Physical (mm):	612.7 x 423.38~533.38 x 217.24
Physical Without Stand (mm):	612.7 x 390.15 x 56.9

GENERAL

Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 9.0, EAC, UkrSEPRO
--------------	---

PACKAGE CONTENTS:	VG2757V-2K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v2.0; Male-Male) x1, USB Type-C Gen2 Cable (Male-Male) x1, USB Type-C to Type-A 3.2 Gen1 Cable (Male-Male) x1, Quick Start Guide x1
-------------------	---

Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
-------------------	--

Warranty:	*Warranty offered may differ from market to market
-----------	--

Power Management:	Energy Star standards, EPEAT
-------------------	------------------------------