

ViewSonic® LCD DISPLAY

VG3208-4K

Key Features

- SuperClear® VA panel with 4K UHD 3840 x 2160 resolution
- Height adjustable swivel stand with tilt function
- HDR10 Delivers Stellar Contrast and Color Accuracy
- Dual HDMI and DisplayPort inputs for flexible connectivity
- EnergyStar, EPEAT certified for sustainability



Product Description

The ViewSonic VG3208-4K is a 32" 4K monitor featuring dual HDMI and DisplayPort inputs for business and home use. The optimal screen performance and comfortable viewing are delivered through Eye ProTech technology, and various ViewMode presets. Expand your workspace and experience truly seamless, ergonomic multitasking on just one screen with a VESA-compatible mount at a low power consumption.

1. Menu Control Panel
2. Power In
3. HDMI*2
4. DisplayPort
5. Audio Out
6. VESA Compatible(Wall Mount 100x100mm)

Visit Us www.viewsonic.com



DISPLAY

| | |
|------------------------------|---|
| Display Size (in.): | 32 |
| Viewable Area (in.): | 31.5 |
| Panel Type: | VA Technology |
| Resolution: | 3840 x 2160 |
| Resolution Type: | UHD (Ultra HD) |
| Static Contrast Ratio: | 3,000:1 (typ) |
| Dynamic Contrast Ratio: | 50M:1 |
| High Dynamic Range: | HDR10 |
| Light Source: | LED |
| Brightness: | 300 cd/m ² (typ) |
| Colors: | 16.7M |
| Color Space Support: | 8 bit true |
| Aspect Ratio: | 16:9 |
| Response Time (Typical GTG): | 4ms |
| Response Time (GTG w/OD): | 4.34ms |
| Viewing Angles: | 178° horizontal, 178° vertical |
| Backlight Life (Hours): | 30000 Hrs (Min) |
| Curvature: | Flat |
| Refresh Rate (Hz): | 60 |
| Low Blue Light: | Software solution |
| Flicker-Free: | Yes |
| Color Gamut: | NTSC: 72% size (Typ) sRGB: 104% size (Typ) |
| Pixel Size: | 0.182 mm (H) x 0.182 mm (V) |
| Surface Treatment: | Anti-Glare, Hard Coating (3H) |

COMPATIBILITY

| | |
|------------------------|--|
| PC Resolution (max): | 3840x2160 |
| Mac® Resolution (max): | 3840x2160 |
| PC Operating System: | Windows 10/11 certified; macOS tested |
| Mac® Resolution (min): | 3840x2160 |

CONNECTOR

| | |
|---------------------------|-----------------------------|
| 3.5mm Audio Out: | 1 |
| HDMI 2.0 (with HDCP 2.2): | 2 |
| DisplayPort: | 1 |
| Power in: | DC Socket (Center Positive) |

POWER

| | |
|------------------------|------------------------|
| Eco Mode (Conserve): | 25W |
| Eco Mode (optimized): | 33W |
| Consumption (typical): | 40W |
| Consumption (max): | 42W |
| Voltage: | AC 100-240V |
| Stand-by: | 0.5W |
| Power Supply: | External Power Adaptor |

ADDITIONAL HARDWARE

| | |
|-----------------------|-----|
| Kensington Lock Slot: | 1 |
| Cable Organization: | Yes |

CONTROLS

| | |
|--------------------|---|
| Physical Controls: | Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) |
| On Screen Display: | Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu |

OPERATING CONDITIONS

| | |
|----------------------------|-----------------------------|
| Temperature: | 32°F to 104°F (0°C to 40°C) |
| Humidity (non-condensing): | 20% to 90% |

WALL MOUNT

| | |
|------------------|--------------|
| VESA Compatible: | 100 x 100 mm |
|------------------|--------------|

INPUT SIGNAL

| | |
|-----------------------|--|
| Frequency Horizontal: | HDMI (v2.0): 15 ~ 140KHz, DisplayPort (v1.4): 24 ~ 140KHz |
| Frequency Vertical: | HDMI (v2.0): 24 ~ 60Hz, DisplayPort (v1.4): 48 ~ 60Hz |

VIDEO INPUT

| | |
|---------------|---|
| Digital Sync: | TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4) |
|---------------|---|

ERGONOMICS

| | |
|----------------------|-----------|
| Height Adjust (mm): | 90 |
| Swivel: | 360° |
| Tilt (Forward/Back): | -4° / 20° |

WEIGHT (IMPERIAL)

| | |
|--------------------------|------|
| Net (lbs): | 17.4 |
| Net Without Stand (lbs): | 12.1 |
| Gross (lbs): | 21.6 |

WEIGHT (METRIC)

| | |
|-------------------------|-----|
| Net (kg): | 7.9 |
| Net Without Stand (kg): | 5.5 |
| Gross (kg): | 9.8 |

DIMENSIONS (IMPERIAL) (WXHXD)

| | |
|-------------------------------|----------------------------|
| Packaging (in.): | 34.4 x 20.3 x 5.8 |
| Physical (in.): | 28.12 x 17.95~21.49 x 8.39 |
| Physical Without Stand (in.): | 28.12 x 16.83 x 2.33 |

DIMENSIONS (METRIC) (WXHXD)

| | |
|------------------------------|------------------------|
| Packaging (mm): | 875 x 515 x 147 |
| Physical (mm): | 714.3 x 456~546 x 213 |
| Physical Without Stand (mm): | 714.3 x 427.48 x 59.22 |

GENERAL

| | |
|-------------------|--|
| Regulations: | Energy Star, EPEAT, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO |
| PACKAGE CONTENTS: | VG3208-4K x1, HDMI Cable (v2.0; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) |
| Recycle/Disposal: | Please dispose of in accordance with local, state or federal laws. |
| Warranty: | *Warranty offered may differ from market to market |
| Power Management: | Energy Star standards, EPEAT |