

Key **Features**

- Find your perfect view every time with the adjustable kickstand.
- Crush lag with a lightning-fast 144Hz refresh rate.
- Enjoy smooth, tear-free gameplay with AMD FreeSync.
- Keep your gear safe on the go with the durable monitor sleeve.
- Plug and play with a single USB-C or mini-HDMI cable.



Product **Description**

Take your gaming anywhere with the ViewSonic VX1654 portable monitor. Built for gamers who demand more, this ultra-sleek, lightweight display features a vibrant Full HD IPS panel that makes every game burst with stunning detail. With AMD FreeSync and a 144Hz refresh rate, you'll enjoy buttery-smooth gameplay free from the hassle of screen tearing or lag. Whether you're at home or on the move, just plug in via USB-C or mini-HDMI, and you're instantly ready for victory.



AIVI	VX 1034 10 144112 II 3 I 0	Trable Garring Mornton - ViewSorne L	urope
DISPLAY		CONTROLS	
Display Size (in.):	16	Physical Controls:	Up, Right, Down, Left, Power
Viewable Area (in.):	15.6	On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Panel Type:	IPS Technology		
Resolution:	1920 x 1080	OPERATING CONDITIONS	Werte
Resolution Type:	FHD (Full HD)	Temperature:	32°F to 104°F (0°C to 40°C)
Static Contrast Ratio:	800:1 (typ)	Humidity (non-condensing):	20% to 90%
Dynamic Contrast Ratio:	80M:1	7.	2070 to 5070
Light Source:	LED	Frequency Horizontal:	mini HDMI (v2.0): 24 ~ 165KHz, Type C: 165 ~ 165KHz
Brightness:	250 cd/m² (typ)		
Colors:	16.7M		mini HDMI (v2.0): 48 ~
Color Space Support:	8 bit (6 bit + FRC)	Frequency Vertical:	144Hz, Type C: 48 ~ 144Hz
Aspect Ratio:	16:9	VIDEO INPUT	
Response Time (GTG w/OD):	4.67ms	Digital Sync:	TMDS - mini HDMI (v2.0), Micro-Packet - Type C
Viewing Angles:	170° horizontal, 170° vertical	ERGONOMICS	- Wildre F doket Type o
Backlight Life (Hours):	15000 Hrs (Min)	Tilt (Forward/Back):	30° / 53°
Curvature:	Flat	WEIGHT (IMPERIAL)	
Refresh Rate (Hz):	144	Net (lbs):	1.5
Variable Refresh Rate	FreeSync	Net Without Stand (lbs):	1.5
Technology:	·	Gross (lbs):	3.5
Low Blue Light:	Software solution	WEIGHT (METRIC)	
Color Gamut:	NTSC: 45% size (Typ) sRGB: 64% size (Typ)	Net (kg):	0.7
Pixel Size:	0.179 mm (H) x 0.179 mm (V)	Net Without Stand (kg):	0.7
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Gross (kg):	1.6
COMPATIBILITY		DIMENSIONS (IMPERIAL) (WX	(HXD)
PC Resolution (max):	1920x1080	Packaging (in.):	17.6 x 15.1 x 3.7
Mac® Resolution (max):	1920x1080	Physical (in.):	14.14 x 8.94 x 0.7
PC Operating System:	Windows 10/11 certified; macOS tested	Physical Without Stand (in.):	14.14 x 8.94 x 0.7
Mac® Resolution (min):	1920x1080	DIMENSIONS (METRIC) (WXH	
CONNECTOR III		Packaging (mm):	446 x 383 x 93
USB 3.2 Type C DisplayPort Alt	2 (60W power charger)	Physical (mm):	359.26 x 226.98 x 17.85
mode only :	, ,	Physical Without Stand (mm):	359.26 x 226.98 x 17.85
3.5mm Audio Out:	1	GENERAL	
Mini HDMI: Power in:	USB Type C (with video & data) 3. Audio Out	Regulations:	cTUVus, FCC-B, ICES003, Energy Star, CEC, NRCan, CE, CE EMC, CB, RoHS, Erf REACH, WEEE, EAC, UkrSEPRO, BSMI
AUDIO	4. lov Kev		VX1654 x1, mini HDMI to
Internal Speakers: POWER	0.8Watts x2	PACKAGE CONTENTS:	HDMI Cable (v1.4; Male- Male) x1, USB Type-C Cable
Eco Mode (Conserve):	9.5W		(Male-Male) x1, Quick Start Guide x1, Sleeve case x1
Eco Mode (optimized):	10.4W		Please dispose of in
Consumption (typical):	11.3W	Recycle/Disposal:	accordance with local, state or federal laws.
Consumption (max):		V. Warranty:	*Warranty offered may differ
Voltage:	DC 5V/9V/12V/15V/20V	vvarranty.	from market to market
Stand-by:	0.5W	Power Management:	Energy Star standards
Power Supply:	External (Optional)		
ADDITIONAL HARDWARE	External (Optional)		
Kensington Lock Slot:	1		
Renampton Luck Sidt.	1		