ViewSonic Market VX2728J

Key Features

- Fast IPS Display with HDR10
- AMD FreeSync[™] Premium for smooth gameplay
- VESA AdaptiveSync for tear-free gaming experience
- VESA ClearMR for clarity of action
- Rapid 0.5ms MPRT for crisp image



Product **Description**

No matter how often you game or when you game, you always win with the Omni VX2728J. The triple certification of AMD FreeSync[™] Premium, VESA Adaptive Sync, and VESA clearMR allows you to savor distortion-free gaming and enhanced clarity. The sharp frames and outstanding color performance are delivered by a fast IPS panel, while the VX2728J's high 165Hz refresh rate supports smooth visuals and minimal input lag. You may think it doesn't get better than this, but it does. Not only will you get the job done — be it grueling gaming sessions, video and photo editing, or office assignments — you'll be working on a sleek, beautifully designed monitor.

Visit Us www.viewsonic.com



VX2728J 27" 165Hz Fast IPS Gaming Monitor

	V/27200		
DISPLAY		VIDEO INPUT	
Display Size (in.):	27	Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.4)
Viewable Area (in.):	27	ERGONOMICS	
Panel Type:	IPS Technology	Height Adjust (mm):	130
Resolution:	1920 x 1080	Swivel:	30°
Resolution Type:	FHD (Full HD)	Tilt (Forward/Back):	-5° / 20°
Static Contrast Ratio:	1,000:1 (typ)	Pivot (Right/Left):	90° / 0°
Dynamic Contrast Ratio:	80M:1	WEIGHT (IMPERIAL)	
Light Source:	LED	Net (lbs):	10.4
Brightness:	250 cd/m² (typ)	Net Without Stand (Ibs):	8
Colors:	16.7M	Gross (lbs):	14.3
Color Space Support:	8 bit (6 bit + FRC)	WEIGHT (METRIC)	
Aspect Ratio:	16:9	Net (kg):	4.7
Response Time (MPRT):	0.5ms	Net Without Stand (kg):	3.7
Viewing Angles:	178º horizontal, 178º vertical	Gross (kg):	6.5
Backlight Life (Hours):	30000 Hrs (Min)	DIMENSIONS (IMPERIAL) (W)	(HXD)
Curvature:	Flat	Packaging (in.):	26.8 x 18.1 x 6.8
Refresh Rate (Hz):	165	Physical (in.):	24.2 x 17.24~22.36 x 8.1
Variable Refresh Rate	FreeSync Premium, AdaptiveSync	Physical Without Stand (in.):	24.2 x 14.3 x 1.8
Technology:		DIMENSIONS (METRIC) (WXH	IXD)
Blue Light Filter:	Yes	Packaging (mm):	680 x 460 x 173
Flicker-Free:	Yes	Physical (mm):	615 x 438~568 x 207
Color Gamut:	DCI-P3: 90% coverage (Typ) NTSC: 94% size (Typ)	Physical Without Stand (mm):	615 x 364 x 46
	sRGB: 132% size (Typ)	GENERAL	
Pixel Size:	0.311 mm (H) x 0.311 mm (V)		cTUVus, FCC-B, ICES003, CEC,
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Regulations:	NRCan, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC,
COMPATIBILITY			UkrSEPRO, UKCA, BSMI, RCM, GEMS, VCCI, PSE
PC Resolution (max):	1920x1080		VX2728J x1, 3-pin Plug (IEC C13 /
Mac® Resolution (max): PC Operating System:	1920x1080 Windows 10/11 certified; macOS tested	PACKAGE CONTENTS:	CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
Mac® Resolution (min):	1920x1080	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
CONNECTOR		Warranty:	*Warranty offered may differ from market to market
3.5mm Audio Out:	1	Hanany.	
HDMI 1.4:	2		
DisplayPort:	1		
Power in:	DC Socket (Center Positive)		
AUDIO			
Internal Speakers:	2Watts x2		
POWER			
Eco Mode (Conserve):	20W		
Eco Mode (optimized):	24W		
Consumption (typical):	29W		
Consumption (max):	33W		
Voltage:	AC 100-240V		
Stand-by:	0.3W		
Power Supply:	External Power Adaptor		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
Cable Organization: CONTROLS	Yes		
Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing): WALL MOUNT	20% to 90%		
VESA Compatible:	100 x 100 mm		
INPUT SIGNAL			
Frequency Horizontal:	HDMI (v1.4): 30 ~ 166KHz, DisplayPort (v1.4): 30 ~ 193KHz		
	HDMI (v1.4): 48 ~ 144Hz, DisplayPort		



Copyright © ViewSonic Corporation 2000-2023. All rights reserved.