Key Features

- SuperClear® IPS panel ensures wide viewing angles and vibrant colors for immersive gaming
- Experience fluid gameplay with the blazing-fast 180hz refresh rate
- Swift 1ms MPRT ensures razorsharp visuals in fast-paced gaming
- Variable refresh rate technology eliminates screen tearing and reduces stuttering
- HDR10 delivers stellar contrast and color accuracy



Product **Description**

The ViewSonic VX2779-HD-PRO is a versatile 27-inch Full HD monitor designed to elevate your visual experience, whether you're working or gaming. With a high 180Hz refresh rate and lightning-fast 1ms MPRT response time, thismonitor ensures smooth visuals and minimal input lag – ideal for gamers seeking a competitive advantage. Equippedwith SuperClear® IPS technology, it boasts wide viewing angles and breathtaking visuals, perfect for immersivegaming sessions, creative endeavors, and efficient office work. Beyond performance, the monitor's sleek designelevates your workspace aesthetics, combining form and function for a complete package.

Visit Us

www.viewsonic.com

	VAZITOTIBTING	27 Tool 12 Galling Monitor Views	onio Europo
DISPLAY		CONTROLS	
Display Size (in.): Viewable Area (in.):	27 27	Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5
Panel Type:	IPS Technology		(power)
Resolution:	1920 x 1080	On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Resolution Type:	FHD (Full HD)		
Static Contrast Ratio:	1,000:1 (typ)	OPERATING CONDITIONS	2005 to 40405 (000 to
Dynamic Contrast Ratio:	50M:1	Temperature:	32°F to 104°F (0°C to 40°C)
High Dynamic Range:	HDR10	Humidity (non-condensing):	20% to 90%
Light Source:	LED	WALL MOUNT	
Brightness:	250 cd/m² (typ)	VESA Compatible:	100 x 100 mm
Colors:	16.7M	INPUT SIGNAL	
Color Space Support:	8 bit (6 bit + FRC)	Frequency Horizontal:	30 ~ 202KHz
Aspect Ratio:	16:9	Frequency Vertical:	48 ~ 180Hz
Response Time (MPRT):	1ms	VIDEO INPUT	
Viewing Angles:	178° horizontal, 178° vertical	Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort
Backlight Life (Hours):	30000 Hrs (Min)	FREONOMICS	(v1.4)
Curvature:	Flat	ERGONOMICS Tilt (Forward/Back):	-5° / 20°
Refresh Rate (Hz):	180	,	-5- / 20-
Variable Refresh Rate Technology:	FreeSync	WEIGHT (IMPERIAL) Net (lbs):	9
Low Blue Light:	Software solution	Net Without Stand (lbs):	8
Flicker-Free:	Yes	Gross (lbs):	12.1
Color Gamut:	NTSC: 72% size (Typ)	WEIGHT (METRIC)	
Color Gaillut.	sRGB: 104% size (Typ)	Net (kg):	4.1
Pixel Size:	0.311 mm (H) x 0.311 mm (V)	Net Without Stand (kg):	3.7
Surface Treatment:	Anti-Glare, Hard	Gross (kg):	5.5
COMPATIBILITY	Coating (3H)	DIMENSIONS (IMPERIAL) (WXHXD)	
PC Resolution (max):	1920x1080	Packaging (in.):	26.8 x 18.1 x 5.3
Mac® Resolution (max):	1920x1080	Physical (in.):	24.2 x 17.9 x 7.1
Mace Resolution (max).	Windows 10/11	Physical Without Stand (in.):	24.2 x 14.3 x 1.8
PC Operating System:	certified; macOS tested	DIMENSIONS (METRIC) (WXHXD)	
Mac® Resolution (min):	1920x1080	Packaging (mm):	680 x 460 x 135
CONNECTOR		Physical (mm):	615 x 454 x 182
3.5mm Audio Out:	1	Physical Without Stand (mm):	615 x 364 x 46
HDMI 1.4:	2	GENERAL	
DisplayPort:	1		CE, CE EMC, CB, RoHS, ErP, REACH,
Power in:	DC Socket (Center Positive)	Regulations:	WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS, BIS,
POWER			CCC, China RoHS, China Energy Label
Eco Mode (Conserve):	24W		VX2779-HD-PRO x1,
Eco Mode (optimized):	28W	PACKAGE CONTENTS:	3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male- Male) x1, AC/DC Adapter x1, Quick Start
Consumption (typical):	30W		
Consumption (max):	34W		
Voltage:	AC 100-240V		Guide x1
Stand-by:	0.5W External Power	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Power Supply:	Adaptor		*Warranty offered may differ from market to market
ADDITIONAL HARDWARE		Warranty:	
Kensington Lock Slot:	1		

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.