


GNC-65

GaN Charger 65W

2x USB-C PD 65W, 1x USB-A QC 3.0



Supports: PPS, PD 3.1, QC 3.0



Charge up to 3 devices



Multi-plug included



Eco friendly packaging

Charge fast, Charge more

Verbatim's 65W GaN Wall Charger combines two USB-C PD 65W ports and one USB-A QC 3.0 port in a sleek, palm-sized design. Ideal for the office, home or travelling to power your laptop, tablet, smartphone, gaming devices, and more. Its foldable US prongs and replaceable EU and UK plugs make it the ultimate travel companion.

Gallium Nitride (GaN) technology delivers high-powered, fast, efficient charging, generates less heat and allow to have smaller and lighter chargers, making them ultra-portable and ideal for travel.

The GNC-65 charger is made with high-quality, flame-resistant materials and features four safety protection systems to ensure your safety while charging.

GNC-65

GaN Charger 65W

2x USB-C PD 65W, 1x USB-A QC 3.0

General Information				
Material	PC fireproof			
Colour	Black/Grey			
Input Plug Formats	US (Type A) / EU (Type C) / UK (Type G)			
Supported devices	iPhone, iPad, Smartphones, Tablet PCs, MP3/MP4 players, etc.			
Power				
Input	100-240 V AC 50/60Hz 1.5 A (Max)			
Total Output	65W Max			
Single Port Output				
USB-C1 PD 3.0	3.3-11V=3A or 5V=3A or 9V=3A or 12V=3A or 15V=3A or 20V=3.25A (65W max.)			
USB-C2 PD 3.0	3.3-11V=3A or 5V=3A or 9V=3A or 12V=3A or 15V=3A or 20V=3.25A (65W max.)			
USB-A QC 3.0	3.6V-6.5V/3A, 6.5V-9V/2A, 9V-12V/1.5A (18W Max)			
Multiport Output		USB-C1 PD 3.0	USB-C2 PD 3.0	USB-A QC 3.0
USB-C1+USB-C2		Max 45W	Max 18W	-
USB-C1+USB-A		Max 45W	-	Max 18W
USB-C2+USB-A		-	Max 15W (5V=3A)	
USB-C1+USB-C2+USB-A		5V=3A (Max 35W) shared		



USB-C 1 (PPS) Output:

Max PD 65W (when used alone)
PPS mode Max 45W

USB-C 2 (PPS) Output:

Max PD 65W (when used alone)
PPS mode Max 45W

USB-A QC 3.0 Output:

Max 30W (when used alone)



EU
Type C



UK
Type G



US
Type A

GNC-65

GaN Charger 65W

2x USB-C PD 65W, 1x USB-A QC 3.0

Other Features	
Compliance	EN 55032:2015+A11:2020+A1:2020 EN 55035:2017+A11:2020 EN IEC 61000-3-2:2019+A1:2020 EN 61000-3-3:2013+A1:2019+A2:2021 EN IEC 62368-1:2020+A11:2020
ROHS compliance	Yes
Output short circuit protect	On short circuit protection situation, will stop charging to protect devices
Over-voltage protection	Yes
Over-current protection	Yes
Over-temperature protection	Yes

PN	Description	Bar Code	EAN128 Code	EAN14 Code
32201	Verbatim GNC-65 GaN Charger 65W with 2 x USB-C® PD 65W / 1 x USB-A QC 3.0 (EU/UK/US)	023942322016	(02)00023942322016(37)10(91)892 (02)00023942322016(37)40(91)892	20023942322010 50023942322011

Logistic Information	
Product Dimensions L x W x H	58.7 x 29.4 x 47.3mm
Product Weight	105 grams
Units per Pack	1
Pack Dimensions L x W x H	110 x 47 x 117.5mm
Pack Weight	220 grams (approx)
Units per Inner Carton	10
Inner Carton Dimensions L x W x H	255 x 255 x 131mm
Inner Carton Weight	2400 grams
Units per Outer Carton	40
Outer Carton Dimensions L x W x H	545 x 280 x 302mm
Master Cartons Weight	10400
Master Cartons per Layer	8
Layers per Pallet	3
Units per Pallet	960



GNC-65

GaN Charger 65W

2x USB-C PD 65W, 1x USB-A QC 3.0



Front



Angled



EU Plug



UK Plug



US Plug



Pack content



Packaging flat



Packaging 3D

Pack Contents:

- GaN Charger
- EU adapter
- UK adapter
- Quick Start Guide

Warning

- INDOOR USE ONLY