

Data Sheet

Fujitsu PRIMERGY RX1330 M6 Rack Server



Cost-efficient, compact platform with exceptional flexibility

Fujitsu offers a fantastic blend of systems, solutions and expertise to guarantee maximum productivity, efficiency and flexibility, delivering confidence and reliability. Fujitsu PRIMERGY servers deliver workload-optimized x86 industry standard systems for any workload and business demand. Since there is no single server solution to meet all these needs, Fujitsu offers a broad server portfolio consisting of expandable tower servers, versatile rack-mount servers, density-optimized multi-node servers as well as GPU servers purpose-built for the demands of AI and VDI. While all these systems are designed to handle multiple workloads, each server is optimized for specific use cases. Whatever the size of your business – large enterprise with multiple sites, or a small or medium-sized company with limited space and budget – with the right choice of server, your IT can become the business enabler you have always wanted it to be.

PRIMERGY RX1330 M6

The Fujitsu PRIMERGY RX1330 M6 server is a mono-socket 1U rack server designed for small businesses as well as remote/branch offices that require reliability, performance and serviceability to support their critical business and customer data needs. The PRIMERGY RX1330 M6 delivers the flexibility to increase compute, storage, and memory capacity. The server can be equipped with the latest Intel® Xeon® E-2400 processors and provides the ability to run multiple applications at the same time, by choosing either a 4-, 6-, or 8-core CPU as well as to address data sets with up to four DDR5 UDIMMs and with a maximum of 128GB of RAM at up to 4,400 MT/s. Intel® Pentium® processors are also available as an option. It provides versatile storage options with up to 4x 3.5" or up to 10x 2.5" storage devices to be able to harness data growth as well as M.2 devices to be used as flash boot device for VMware environments. Moreover, there is an additional

version based on a chassis with a shorter depth (less than 450mm) especially suited for network service providers. Equipped with two PCIe 5.0, one PCIe 4.0 expansion slots and 2x Gbit LAN onboard, the PRIMERGY RX1330 M6 offers improved data transfer rates and higher networking speeds. By delivering high energy efficient PSUs (96% Titanium), with the choice between standard and redundant power supplies as well as a modular approach for RAID and LAN controllers, the mono-socket server contributes to reduced operational costs. It provides a simple design for easy serviceability and comes along with the latest integrated Remote Management Controller (iRMC S6) to simplify server management. Integrated security and proven reliability helps to ensure maximum uptime. In addition to some enhanced security protections for application data such as Intel SGX, the server also offers a lockable front bezel to avoid unauthorized physical access directly in the datacenter.



Features & Benefits

| Main Features | Benefits |
|--|---|
| <p>BOOST YOUR PRODUCTIVITY</p> <ul style="list-style-type: none"> ■ Increase compute performance and the ability to run multiple applications at the same time, by choosing either a 4-, 6-, or 8-core Intel® Xeon® E-2400 processors, or the option to use more affordable Intel® Pentium® processors. <p>SCALE YOUR IT ACCORDING TO YOUR NEEDS</p> <ul style="list-style-type: none"> ■ Harness data growth with up to 4x 3.5" or up to 10x 2.5" storage devices as well as M.2 devices to be used as flash boot device for VMware environments. <p>SIMPLIFY YOUR IT</p> <ul style="list-style-type: none"> ■ Embedded with iRMC S6 for remote access of your servers anywhere and anytime. In addition, Infrastructure Manager (ISM) provides seamless, holistic management ensuring that IT infrastructures retain the dynamic flexibility required to support ever-changing business demands. Two versions of ISM are available. ISM Advanced is a powerful, fully featured version offering comprehensive infrastructure management capabilities such as support for multiple hardware configurations, physical and virtual network connection indicators and firmware baseline updates. A free entry-level version, ISM Essential, provides essential monitoring and firmware update of all supported devices, including servers, storage and network switches. <p>GROW YOUR BUSINESS</p> <ul style="list-style-type: none"> ■ Address data sets with up to four DDR5 DIMMs and with a maximum of 128GB of RAM up to 4,400 MT/s. In addition, the server can be expanded using up to two PCIe 5.0 and one PCIe 4.0 slots. | <ul style="list-style-type: none"> ■ Workload optimized performance for space and power constrained environments from the edge to the data center. ■ The PRIMERGY RX1330 M6 delivers the flexibility to increase compute, storage, and memory capacity based on various configuration options and different base units. ■ New iRMC S6 enhances server administrator productivity with a variety of user-friendly features for remote management. Moreover, Infrastructure Manager (ISM) enables organizations to have centralized control over the entire infrastructure using a single user interface. ■ The variety of expansion options makes the RX1330 M6 an ideal rack server platform for growing businesses. Outstanding configuration flexibility caters to a variety of business requirements and a range of HPE Qualified Options to fit most needs. |

Technical details

PRIMERGY RX1330 M6

| | | | | | | | |
|----------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| Base unit | RX1330 M6 (8x 2.5") | RX1330 M6 (8x 2.5") | RX1330 M6 (4x 3.5") | RX1330 M6 (4x 3.5") | RX1330 M6 (4x 2.5") | RX1330 M6 (10x 2.5") | RX1330 M6 (4x 2.5") |
| Housing types | Rack | Rack | Rack | Rack | Rack (short depth) | Rack | Rack (short depth) |
| Storage drive architecture | 2.5-inch SAS/SATA | 2.5-inch SAS/SATA | 3.5-inch SAS/SATA | 3.5-inch SAS/SATA | 2.5-inch SAS/SATA | 2.5-inch SAS/SATA | 2.5-inch SAS/SATA |
| Power supply | Hot-plug | Standard | Hot-plug | Standard | Standard | Hot-plug | Hot-plug |
| Product Type | Mono Socket Rack Server | Mono Socket Rack Server | Mono Socket Rack Server | Mono Socket Rack Server | Mono Socket Rack Server | Mono Socket Rack Server | Mono Socket Rack Server |

Mainboard

| | |
|-----------------------------|--|
| Mainboard type | D4133 |
| Chipset | Intel® C266 |
| Processor quantity and type | 1 x Intel® Xeon® E-2400 processor family / Intel® Pentium® processor |

Processor

| | |
|-------------------------------|---|
| | Intel® Xeon® processor E-2488 (8C/16T, 3.20 GHz, TLC: 24 MB, Turbo: 5.20 GHz, 4,800MHz, 95 W) |
| | Intel® Xeon® processor E-2486 (6C/12T, 3.50 GHz, TLC: 18 MB, Turbo: 5.20 GHz, 4,800MHz, 95 W) |
| | Intel® Xeon® processor E-2478 (8C/16T, 2.80 GHz, TLC: 24 MB, Turbo: 4.50 GHz, 4,800MHz, 80 W) |
| | Intel® Xeon® processor E-2468 (8C/16T, 2.60 GHz, TLC: 24 MB, Turbo: 4.40 GHz, 4,800MHz, 65 W) |
| | Intel® Xeon® processor E-2456 (6C/12T, 3.30 GHz, TLC: 18 MB, Turbo: 4.60 GHz, 4,800MHz, 80 W) |
| | Intel® Xeon® processor E-2436 (6C/12T, 2.90 GHz, TLC: 18 MB, Turbo: 4.40 GHz, 4,800MHz, 65 W) |
| | Intel® Xeon® processor E-2434 (4C/8T, 3.40 GHz, TLC: 12 MB, Turbo: 4.60 GHz, 4,800MHz, 55 W) |
| | Intel® Xeon® processor E-2414 (4C/4T, 2.60 GHz, TLC: 12 MB, Turbo: 4.30 GHz, 4,800MHz, 55 W) |
| | Intel® Pentium® Gold G7400 (2C/4T, 3.70 GHz, TLC: 6 MB, Turbo: No, 4,800 MHz, 46 W) |
| Memory slots | 4 |
| Memory slot type | UDIMM (DDR5) |
| Memory capacity (min. - max.) | 16 GB - 128 GB |
| Memory protection | ECC |
| Memory notes | Single channel memory configuration : max. 4,400 MT/s Dual channel memory configuration(1R) : max. 4,000 MT/s Dual channel memory configuration(2R) : max. 3,600 MT/s |

Interfaces

| | |
|-----------------------|--|
| USB 3.x ports | 7 (Rear: 4x 3.2 Gen1 for all base units, Front (except 10x 2.5" base unit): 2x USB 3.2 Gen1, 1x USB 3.2 Gen2(20 Gb, Type C) , Front (for 10x 2.5" base unit): 2x USB 3.2 Gen1) |
| Graphics (15-pin) | 1 x VGA (15-pin) / optional 1 x front VGA (not for 10x 2.5" base unit) |
| Serial connection | 1 x optional (occupies PCIe slot) |
| LAN / Ethernet | 2 |
| Management LAN (RJ45) | 1 x dedicated management LAN port for iRMC S6 (10/100/1000 Mbit/s) Management LAN traffic can be switched to shared onboard Gbit LAN port |

Onboard or integrated Controller

| | |
|-------------------------------|---|
| RAID controller | Integrated RAID 0/1 or RAID 5/6 controller (option) All hardware storage controller options are described under Components |
| SATA Controller | Intel® C266, 1x SATA channel for ODD, 2x SATA channel for M.2, 4x SATA channel for HDD/SSD |
| LAN Controller | Intel® i210 onboard 2 x 10/100/1000 Mbit/s Ethernet (TCP/IP acceleration) |
| Remote management controller | Integrated Remote Management Controller (iRMC S6, 1024 MB attached memory incl. graphics controller) |
| Trusted Platform Module (TPM) | TPM 2.0 module (option) |

Slots

| | |
|--------------------|---|
| PCI-Express 5.0 x8 | 2 x Low Profile |
| Slot Notes | Optional support of 1x Full Height PCIe 5.0 x8 card, instead of 1x Low Profile PCIe 4.0 x4 and 1x Low Profile PCIe 5.0 x8 |

| Drive bays | | | | | |
|--|--|-----------------------------------|-----------------------------------|-------------------|-------------|
| Storage drive bays | 4/8 x 2.5-inch hot-plug SATA/SAS or 4x 3.5-inch hot-plug or 10 x 2.5-inch hot-plug SATA/SAS | | | | |
| Accessible drive bays | 1 x 5.25/9.5mm for DVD-RW/Blu-ray | | | | |
| Notes accessible drives | Not for 10x 2.5-inch HDD base unit. All possible options described in relevant system configurator. | | | | |
| Drive bays (Base unit specific) | | | | | |
| Storage drive bays | Max. 8x 2.5-inch | Max. 4x 3.5-inch | 4x 2.5-inch | Max. 10x 2.5-inch | 4x 2.5-inch |
| Accessible drive bays | 1 x 5.25/9.5mm for DVD-RW/Blu-ray | 1 x 5.25/9.5mm for DVD-RW/Blu-ray | 1 x 5.25/9.5mm for DVD-RW/Blu-ray | | |
| Fan Configuration | | | | | |
| Number of fans | 5 | | | | |
| Fan notes | 5 single non hot-plug fans or 5 dual non hot-plug fans (4+1 redundancy, depends on system configuration) | | | | |
| Operating panel | | | | | |
| Operating buttons | On/off switch NMI button Reset button ID button | | | | |
| Status LEDs | At system front side: Power (DC-On: green / AC-On: white) Global error (orange) Identification (blue) Hard disks access (green) CSS (orange) At system rear side: CSS (orange) Identification (blue) Global error (orange) LAN connection (green) LAN speed (green / yellow) | | | | |
| BIOS | | | | | |
| BIOS features | UEFI compliant Secure boot support ROM based setup utility Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Linux versions Local and remote update via ServerView Update Manager Remote PXE boot support Remote iSCSI boot support HTTP and HTTPS Boot | | | | |
| Operating Systems and Virtualization Software | | | | | |
| Certified or supported operating systems and virtualization software | Windows Server 2022 Datacenter Windows Server 2022 Standard Windows Server 2022 Essentials VMware vSphere™ 8.0 SUSE® Linux Enterprise Server 15 Red Hat® Enterprise Linux 8 | | | | |
| Operating system release link | http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473 | | | | |
| Operating system notes | Use of certified or supported operating systems and virtualization software is subject to proactive acceptance of the respective License Agreements/ EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration. | | | | |
| Infrastructure and Server Management | | | | | |
| DC Infrastructure Management | Infrastructure Manager (ISM) Essential Edition Advanced Edition | | | | |

Infrastructure and Server Management

| | |
|--------------------|--|
| Server Management | Infrastructure Manager (ISM) ServerView Agentless Service (SVAS) ServerView ESXi CIM Provider ServerView Installation Manager (SVIM) ServerView embedded Lifecycle Management (eLCM) Lifecycle management |
| Management notes | For further information regarding ISM see dedicated data sheets. |
| Manageability link | http://docs.ts.fujitsu.com/dl.aspx?id=9e92297a-16fb-4c69-8559-e38e7b42fee6 |

Dimensions / Weight

| | |
|----------------------|--|
| Rack (W x D x H) | 483 mm (Bezel) / 436 mm (Body) x 556 (including protrusion: 612) x 43 mm |
| Dimension notes | Short depth: 483 mm (Bezel) / 436 mm (Body) x 448 (including protrusion: 506) mm x 43 mm |
| Height Unit Rack | 1 U |
| Weight | Standard: max. 13.1 kg [17.7 kg(including RMK/CMA)] Short depth: max. 9.5 kg [13.8 kg(including RMK/CMA)] |
| Weight notes | Actual weight may vary depending on configuration |
| Rack integration kit | Rack integration kit as option |

Environment

| | |
|-------------------------------|---|
| Operating ambient temperature | 5 - 45 °C (41 - 113 °F) |
| Operating temperature note | Cool-safe® Advanced Thermal Design (above 35 °C or below 10 °C) depending on configuration. Please use the Fujitsu WebArchitect (www.fujitsu.com/configurator/public) to get detailed information on the corresponding configurations. |
| Operating relative humidity | 8 - 85 % (non condensing) |
| Operating environment | FTS 04230 – Guideline for Data Center (installation specification) |
| Operating environment link | http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe |
| Noise emission | Measured according to ISO 7779 and declared according to ISO 9296 |
| Sound pressure (LpAm) | Minimum configuration: 21 dB(A) (idle) / 21 dB(A) (operating) Typical configuration: 21 dB(A) (idle) / 21 dB(A) (operating) Maximum configuration: 36 dB(A) (idle) / 42 dB(A) (operating) [With GPU/NVMe M.2 SSD] |
| Sound power (LWA; 1B = 10dB) | Minimum configuration: 4.0 B (idle) / 4.0 B (operating) Typical configuration: 4.0 B (idle) / 4.0 B (operating) Maximum configuration: 5.4 B (idle) / 5.9 B (operating) [With GPU/NVMe M.2 SSD] |
| Noise notes | Noise emissions and operation modes depend on system configuration. |

Electrical values

| | |
|-------------------------------------|---|
| Power supply configuration | 1x standard power supply or 1x hot-plug power supply or 2x hot-plug power supplies for redundancy depending on model |
| Hot-plug power supply redundancy | Optional |
| Active power (max. configuration) | 494 W |
| Apparent power (max. configuration) | 496 VA |
| Heat emission (max. configuration) | 1778.4 kJ/h (1685.6 BTU/h) |
| Rated current max. | 11A (100V) / 5.7A (240V) |
| Active power note | To estimate the power consumption of different configurations please use the Fujitsu WebArchitect: www.fujitsu.com/configurator/public |
| Power supply | 400W standard, 92%(Platinum efficiency), 100-240V, 50/60Hz 500W hot-plug, 96% (Titanium efficiency), 200-240V, 50 / 60Hz 900W hot-plug, 96% (Titanium efficiency), 200-240V, 50 / 60Hz |
| Power supply notes | Power Safeguard adapts system performance in case the power requirements exceeds supply limits. Platinum PSUs are only for APAC/Japan market. |
| Battery backup | Fujitsu Battery Unit 380W, 12V (as option) |

Compliance

| | |
|---------|---|
| Product | PRIMERGY RX1330 M6 |
| Model | PR1330B/PR1330BS |
| Global | CB RoHS (Substance limitations in accordance with global RoHS regulations) WEEE (Waste electrical and electronic equipment) |

Compliance

| | |
|-----------------------|---|
| Germany | GS |
| Europe | CE |
| USA/Canada | NRTLc/us FCC Class A ICES-003 / NMB-003 Class A |
| Japan | VCCI Class A + JIS 61000-3-2 |
| Russia | EAC |
| South Korea | KC |
| China | CCC |
| Australia/New Zealand | RCM |
| Taiwan | BSMI |
| India | BIS |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates |
| Compliance notes | There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures. |

Components

Optical drives

Blu-ray Disc™ Triple Writer, (6x BD-RW, 8x DVD, 24x CD), ultraslim, SATA I
DVD Super Multi ultra slim , (8x DVD; 24x CD), ultraslim, SATA I

SSD SATA 2.5-inch

| |
|--|
| SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.5 DWPD |
| SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED |
| SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD |
| SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 5.0 DWPD |
| SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD, SED |
| SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.0 DWPD |
| SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.5 DWPD |
| SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED |
| SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD |
| SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 5.0 DWPD |
| SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD, SED |
| SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.0 DWPD |
| SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.5 DWPD |
| SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD |
| SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED |
| SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD |
| SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.6 DWPD |
| SSD SATA, 6 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.2 DWPD |
| SSD SATA, 6 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED |
| SSD SATA, 6 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD |
| SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.5 DWPD |
| SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD, SED |
| SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.0 DWPD |
| SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.5 DWPD |
| SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED |
| SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD |
| SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 5.0 DWPD |
| SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD, SED |
| SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.0 DWPD |

| | | |
|---|--|--|
| SSD SATA 3.5-inch | SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.5 DWPD | |
| | SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD, SED | |
| | SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.0 DWPD | |
| | SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 5.0 DWPD | |
| | SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD, SED | |
| | SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3.0 DWPD | |
| | SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.5 DWPD | |
| | SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD, SED | |
| | SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.0 DWPD | |
| | SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 5.0 DWPD | |
| | SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD, SED | |
| | SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3.0 DWPD | |
| | SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.5 DWPD | |
| | SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.0 DWPD | |
| | SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD, SED | |
| | SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.0 DWPD | |
| | SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 0.6 DWPD | |
| | SSD SATA, 6 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.2 DWPD | |
| | SSD SATA, 6 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD, SED | |
| | SSD SATA, 6 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.0 DWPD | |
| | SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3.5 DWPD | |
| | SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD, SED | |
| | SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3.0 DWPD | |
| | SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.5 DWPD | |
| | SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD, SED | |
| | SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.0 DWPD | |
| | SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 5.0 DWPD | |
| | SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD, SED | |
| | SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3.0 DWPD | |
| | SCSI / SAS Controller | Fujitsu PSAS CP 2200-16i LP Host Bus Adapter 24 Gbit/s 16 GT/s 16 ports int. |
| | | Broadcom® PSAS CP600e LP SAS Ctrl. 12 Gbit/s PCIe 3.0 x8 |
| | RAID Controller | pre-configured RAID1 Array for M.2 in PDUAL, |
| Fujitsu PRAID EP680i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 16 GT/s, 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 8 GB, Optional FBU based on LSI SAS3916 | | |
| Fujitsu PRAID EP640i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3908 | | |
| Fujitsu PRAID EP 3252-8i LP, RAID 5/6 Ctrl., SAS/SATA 24 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU | | |
| Broadcom® PRAID CP600i LP, RAID Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, No FBU support | | |
| Fibre Channel controller | Fibre Channel Host Bus Adapter 1 x Qlogic QLE2770-FJ-BK LC-style | |
| | Fibre Channel Host Bus Adapter 2 x Qlogic QLE2772-FJ-BK LC-style | |
| | Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Qlogic QLE2690 LC-style | |
| | Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Qlogic QLE2692 LC-style | |
| GPU computing card | NVIDIA® A2, 200GB/s, 16GB GDDR6, N/A, PCIe 4.0 x8 | |
| | -, xxxGB/s, 24GB GDDR6, N/A, PCIe 4.0 x16 | |
| | NVIDIA® T400 4GB, 4 GB, 384 cores, 4GB, N/A, PCIe x16, 3 x miniDP | |

| | |
|---------------------|---|
| Rack infrastructure | Rackmount kit full extraction (665mm). tool less mounting for general use, length variable 559-890mm. If consider to shipment with Rack and earthquake, suggest to fix RMK with security screw. |
| | Rackmount kit full extraction (562.5mm). tool less mounting for general use, length variable 559-890mm. If consider to shipment with Rack and earthquake, suggest to fix RMK with security screw. |
| | Rackmount kit full extraction (495mm). tool less mounting, length variable 440-580mm. |
| | Rackmount kit tool less mounting |
| | Cable Management 1U for PRIMECENTER- and 3rd-party racks |

Notes

| | |
|-----------------------|---|
| Compatibility | If and to the extent a list of components or certain compatibilities are specified in the product data sheet, these component lists and compatibility specifications are exhaustive. Using deviating or other system components and applications together with the product may but does not necessarily have to lead to compatibility problems. A final statement and/or commitment on the compatibility of such deviating or other system components and applications can only be provided after a corresponding verification through a dedicated compatibility testing. |
| Continuity management | The product may in connection with and depending on the specific configuration include elements to support time- and performance-critical applications, however high availability (e.g., 99.9999%) and failsafe performance is not a standalone product feature. If and to the extent the product is to be used in such business-critical environments, it is within the sole responsibility of the user to set up the specific additional technical features (e.g., Storage Cluster), redundancies, and operational conditions as required to ensure such high availability or failsafe performance. |
| Security | The properties of the product provide a baseline for product security and therefore end-customer IT security. However, these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuration options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation. |

Warranty

| | |
|--|---|
| Manufacturer warranty period | 1 year |
| Warranty type | Onsite warranty |
| Warranty Terms & Conditions | www.fujitsu.com/support |
| Product Support - the perfect extension | |
| Support Pack Options | Globally available in major metropolitan areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time (depending on country) 24x7, 4h Onsite Response Time (depending on country) |
| Recommended Service | 24x7 Onsite Service with 4h Onsite Response Time |
| Service Lifecycle | at least 5 years after shipment, for details see https://support.ts.fujitsu.com/ |
| Service Weblink | http://www.fujitsu.com/emeia/products/product-support-services/ |

More information

Fujitsu products, solutions & services

In addition to Fujitsu PRIMERGY RX1330 M6, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY RX1330 M6, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/primergy

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/>
Copyright 2024 Fujitsu LIMITED

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering. The product was developed for normal business use. Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact
Fujitsu LIMITED

Website: www.fujitsu.com
2024-06-06 WW-EN