

Model Name	RS-CA324FKRB-L-LF28W-M	RS-CA358FKRB-L-LF28W-M	RS-CA348T1KRB-L-LF28W-M
Imaging Device	1/2.8" Progressive CMOS	1/2.7" Progressive CMOS	
Scanning System	Progressive Scanning		
Video Output	BNC		
Resolution	2MP 1920(H)×1080(V)	5MP 2608(H)×1960(V)	8MP 3840(H)×2160(V)
Max, Framerate	2MP: TVI/AHD/CVI: PAL@25fps NTSC@30fps 2MP: TVI:15FPS CVBS: 960H	5MP: TVI/AHD: @20fps,TVI@12.5FPS 4MP: TVI/AHD/CVI: PAL@25fps NTSC@30fps 2MP: TVI/AHD/CVI: PAL@25fps NTSC@30fps CVBS: 960H	AHD/TVI/CVI: 8MP@15fps, TVI/CVI: 8MP@12.5fps, CVBS: 960H
Max. Aperture Ratio	F1.0		
Lens Type/ Focal Length	Fixed lens / 3.6mm / 2.8mm		
Audio	Audio over coaxial		
Audio Range	7m		
IR Distance/ Warm Light Viewable Length	30m/20m		
On Screen Display	English		
Day & Night	Color / Ext / B/W		
Backlight Compensation	Auto		
Wide Dynamic Range	DWDR		
Digital Noise Reduction	3D DNR	2D DNR	
Gain Control	Auto		
White Balance	Auto		
Electronic Shutter Speed	Auto		
Reverse	Mirror		
Video Transmission Distance	MAX 300M (Cable : 5C 2V)		
Operating Temperature / Humidity	-30°C ~ 55°C / 90%		
Ingress Protection	IP67		
Input Voltage/Current	12V DC		
Power Consumption	IR OFF ≤ 0.5W, IR ON ≤ 6.2W		
Color / Material	Metal		