

AGAT LED 15W, ogarden luminaire with motion sensor 140st, 1100lm, IP54, 4000K, white

Marka: **ADVITI** | Symbol: **AD-OP-6112WLPMR4** | Ean: **5908254817540**

Adviti



PRODUCT DESCRIPTION

A garden luminaire with a simple shape and a neatly built-in PIR motion sensor, which perfectly illuminates the entrance to the building, driveway, terrace or garden arbors. This outdoor lamp can be mounted on the walls of buildings and even fences. Several identical luminaires mounted at a certain distance from one another will create an interesting and coherent visual effect, and the entrance to the house or office building will be beautifully presented. The luminaire uses SMD LEDs, which guarantee high energy efficiency and have a long service life, because they shine up to 50,000 hours. The presented garden lamp works with rated power of

15W and emits light with luminous flux of 1100 lm. It shines with a natural white color with a temperature of 4000K. The device has a built-in PIR sensor that turns on the light when movement is detected and allows to set the lighting time according to individual preferences (from 10 +/- seconds to 5 +/- minutes). The sensor detects movement both during the day and at night. The maximum detection range is 9 meters. The twilight sensor, depending on the settings, switches the lighting on only when the ambient light intensity is insufficient. The degree of ingress protection IP54 guarantees sufficient protection against dust and water, so this garden luminaire will easily withstand even more difficult weather conditions. The lamp is available in white and black.

TECHNICAL DATA

General information:

| | |
|---|----------------|
| Place of application: | Inside and out |
| Possibility of cooperation with a dimmer: | No |
| Durability L70/B50: | 50000 h |
| Connection type: | Screw cube |
| The minimum distance from the illuminated object: | 0,5 m |
| Luminous flux: | 1100 lm |
| Rated power: | 15 W |
| Light source: | LED SMD |
| Degree of protection (IP): | 54 |
| Colour temperature: | 4000 |
| Beam angle: | 120 ° |
| Nominal voltage: | 230V~, 50Hz |
| Colour: | white |
| Solar panel: | No |
| Dimensions - width: | 210 mm |
| Dimensions - height: | 49 mm |
| Colour rendering index CRI: | >80 |
| Material housing: | PC |
| Detection angle: | 140° |
| Material of the lampshade: | polycarbonate |

| | |
|--|---|
| Control of the motion sensor: | Yes |
| Number of on / off cycles: | 100000 |
| Protection class against electric shock: | II |
| Type of sensor: | PIR |
| Detection range: | 9 m |
| Operating temperature: | - 20 ~ 40°C |
| Adjustable daylight sensor (LUX): | Yes |
| Daylight sensor adjustment range (LUX): | <3–2000lux |
| Adjustable time setting (TIME): | Yes |
| Lighting time adjustment range (TIME): | min: 10 sek. ± 3 sek.; max: 5 min. ± 1 min. |
| Adjustment of motion detection range (SENS): | No |



