

NEFRYT LED 15W, garden luminaire, 1100lm, IP54, 4000K, black

AdvitiMarka: **ADVITI** | Symbol: **AD-OP-6147BLPM4** | Ean: **5908254818646**

PRODUCT DESCRIPTION

A garden luminaire with a simple shape which perfectly illuminates the entrance to the building, driveway, terrace or garden arbors. This outdoor lamp can be mounted on the walls of buildings and even fences. Several identical luminaires mounted at a certain distance from one another will create an interesting and coherent visual effect, and the entrance to the house or office building will be beautifully presented. This luminaire uses SMD LEDs, which guarantee high energy efficiency and have a long service life, because they shine up to 50,000 hours. This lamp suitable for the garden works with rated power of 15W and emits light with

luminous flux of 11000 lm. It shines with a natural white color with a temperature of 4000K. The degree of ingress protection IP54 guarantees sufficient protection against dust and water, therefore this garden luminaire will easily withstand even more difficult weather conditions.

TECHNICAL DATA

General information:

| | |
|---|----------------|
| Place of application: | Inside and out |
| Possibility of cooperation with a dimmer: | No |
| Durability L70/B50: | 50000 h |
| Connection type: | Screw cube |
| The minimum distance from the illuminated object: | 0,5 m |
| Luminous flux: | 1100 lm |
| Rated power: | 15 W |
| Light source: | LED SMD |
| Degree of protection (IP): | 54 |
| Colour temperature: | 4000 |
| Beam angle: | 120 ° |
| Nominal voltage: | 230V~, 50Hz |
| Colour: | black |
| Solar panel: | No |
| Dimensions - depth: | 44.5 mm |
| Dimensions - width: | 212,2 mm |
| Dimensions - height: | 119.2 mm |
| Colour rendering index CRI: | 85 |
| Material housing: | PC |
| Material of the lampshade: | PC |
| Number of on / off cycles: | 100000 |
| Protection class against electric shock: | II |
| Operating temperature: | - 20 ~ 40°C |

| | |
|--|----|
| Adjustable daylight sensor (LUX): | No |
| Adjustment of motion detection range (SENS): | No |



