

# PRODUCT DATASHEET

## ENDURA Style Square 13.5W Dark Gray

ENDURA® STYLE SQUARE | Wall and ceiling luminaires with modern design in square shape



### Areas of application

- Outdoor use (IP44)
- Building facades
- Patios, balconies

### Product benefits

- Energy-efficient thanks to LED technology
- Easy and quick installation

### Product features

- Bright and functional outdoor LED luminaires
- Die-cast aluminum housing
- Available in two housing colors



---

## TECHNICAL DATA

### Electrical data


|   |               |
|---|---------------|
| Nominal wattage   | 13.50 W       |
| Nominal voltage   | 220...240 V   |
| Mains frequency   | 50...60 Hz    |
| Max. number of luminaires per miniature circuit breaker B16 | 100           |
| Max. number of luminaires per miniature circuit breaker C16 | 200           |
| Power factor $\lambda$                                      | > 0.5         |
| Total harmonic distortion                                   | $\leq 20$ %   |
| Protection class  | I             |
| Operating mode  | Mains voltage |

### Photometrical data

|  |                           |
|--|---------------------------|
| Luminous flux                                  | 480 lm                    |
| Total luminous flux of contained light sources | 1450 lm                   |
| Luminous efficacy                              | 37 lm/W                   |
| Color temperature                              | 3000 K                    |
| Light color (designation)                      | Warm White                |
| Color rendering index Ra                       | > 80                      |
| Standard deviation of color matching           | $\leq 6$ sdc <sub>m</sub> |
| Flickering metric (Pst LM)                     | -                         |
| Stroboscope effect metric (SVM)                | -                         |
| Photobiological safety group acc. to EN62778   | RG0                       |
| Beam angle                                     | 100 °                     |
| UGR  | < 25                      |

### Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 202.00 mm |
| Width          | 202.00 mm |
| Height         | 45.00 mm  |
| Product weight | 900.00 g  |



PG ENDURA STYLE Square MiPRC

### Materials & Colors

|                 |                    |
|-----------------|--------------------|
| Product color   | Dark gray          |
| Housing color   | Dark gray          |
| Body material   | Aluminum           |
| Cover material  | Polycarbonate (PC) |
| Mercury content | 0.0 mg             |

### Application & Mounting

|  |                 |
|--|-----------------|
| Ambient temperature range              | -20...+40 °C    |
| Temperature range at storage           | -20...+85 °C    |
| Type of connection                     | Screw terminal  |
| Type of protection                     | IP44            |
| Protection class IK (shock resistance) | IK07            |
| Dimmable                               | No              |
| Mounting type                          | Surface         |
| Mounting location                      | Wall            |
| Application environment                | Outdoor         |
| LED module replaceable                 | Not replaceable |
| With light source                      | Yes             |

### Lifespan

|                            |                       |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C  | 30000 h <sup>1)</sup> |
| Number of switching cycles | 15000                 |

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Certificates & Standards

|  |                 |
|--|-----------------|
| Standards  | CE / EAC / UKCA |
| Luminaire with limited surface temperature, "D sign" | No              |





### Additional product data

|                       |       |
|-----------------------|-------|
| Number of illuminants | empty |
|-----------------------|-------|

### EQUIPMENT / ACCESSORIES

– Complete mounting and connecting accessories included

### DOWNLOAD DATA

|  | Documents and certificates      | Document name                      |
|--|---------------------------------|------------------------------------|
|    | User Instruction                | ENDURA® STYLE Ring Square 13W      |
|    | Legal information               | Legal insert                       |
|   | Declarations of conformity      | CE Declaration Endura Style Square |
|  | Declarations Of Conformity UKCA | Fixed LUM                          |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075205253 | Folding box<br>1             | 65 mm x 237 mm x 228 mm              | 960.00 g     | 3.51 dm <sup>3</sup>  |
| 4058075205260 | Shipping box<br>6            | 470 mm x 255 mm x 215 mm             | 6034.00 g    | 25.77 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.